

	ENGLISH	SI
<b>Performance</b>		
Number of Conductors	1	1
Cable Style	Coaxial	Coaxial
Connector Type(Antenna side)	N	N
Connector Style(Antenna side)	Male	Male
Connection Type(Antenna side)	Threaded	Threaded
Connector Type(Receiver side)	N	N
Connector Style(Receiver side)	Male	Male
Connection Type(Receiver side)	Threaded	Threaded
<b>Environmental</b>		
Temperature Range	-40 to +176 °F	-40 to +80 °C
Pull Strength	160 lb	72.6 kg
<b>Electrical</b>		
Impedance	50 Ohm	50 Ohm
Capacitance	23.5 pF/ft	23.5 pF/ft
<b>Physical</b>		
Cable Jacket Diameter	0.405 in	10.29 mm
Cable Jacket Material	Polyurethane	Polyurethane
Cable Jacket Color	Black	Black
Conductor Material	Copper/Aluminum	Copper/Aluminum
Conductor Diameter	0.108 in	2.74 mm
Insulation Material Over Conductor(s)	Physical Foam Polyethylene	Physical Foam Polyethylene
Shield Type Over Conductor(s)	Copper Braid	Copper Braid
Shield Material Over Conductor(s)	Aluminum Foil	Aluminum Foil
Bend Radius(minimum)	2.0 in	51 mm
Weight	.15 lb-ft	.26 kg-m
ROHS Compliant	Yes	Yes

**OPTIONAL VERSIONS**

Optional versions have identical specifications and accessories as listed for the standard model except where noted below. More than one option may be used.

**NOTES:**

Entered: LK	Engineer: BAM	Sales: MC	Approved: BAM	Spec Number:
Date: 12/17/2019	Date: 12/17/2019	Date: 12/17/2019	Date: 12/17/2019	68407

**PCB PIEZOTRONICS**

 Phone: 716-684-0001  
 Fax: 716-684-0987  
 E-Mail: info@pcb.com

3425 Walden Avenue, Depew, NY 14043

All specifications are at room temperature unless otherwise specified.  
 In the interest of constant product improvement, we reserve the right to change specifications without notice.