

Model Number 039025-54015	ROTARY TORQUE				Revision: NR ECN #: 38721
Performance		ENGLISH	SI		OPTIONAL VERSIONS
Measurement Range(Full Scale Capacity)		132 lbf-in	15 Nm		Optional versions have identical specifications and accessories as listed for the standard model except where noted below. More than one option may be used.
Sensitivity(output at rated capacity)		2.0 mV/V	2.0 mV/V	[5]	
Non-Linearity		≤ 0.25 % FS	≤ 0.25 % FS	[2]	
Hysteresis		≤ 0.25 % FS	≤ 0.25 % FS	[2]	
Non-Repeatability		≤ 0.05 % FS	≤ 0.05 % FS	[2]	
Interchangeability		≤ 0.30 % FS	≤ 0.30 % FS	[6][2]	
Environmental					NOTES:
Overload Limit		203 lbf-in	23 Nm		[1] Calibrated at 10 VDC, usable 5 to 20 VDC or VAC RMS.
Temperature Range(Operating)		0 to +200 °F	-18 to +93 °C		[2] FS - Full Scale.
Temperature Range(Compensated)		+70 to +150 °F	+21 to +66 °C		[3] Matched with 43.575 kOhm Precision Resistor.
Temperature Effect on Output(Maximum)		± 0.002 %Reading/°F	± 0.0018 %Reading/°C	[4]	[4] Over compensated temperature range.
Temperature Effect on Zero Balance(Maximum)		± 0.002 %FS/°F	± 0.0018 %FS/°C	[4]	[5] Matched to ±0.25% F.S.
Electrical					[6] Matched for mV/V and shunt calibration.
Bridge Resistance		350 Ohm	350 Ohm		[7] See Outline Drawing 52048 for Complete Dimensions
Excitation Voltage		10 VDC	10 VDC	[1]	[8] Per ANSI B107.4 Specifications
Insulation Resistance		≥ 5 GOhm	≥ 5 GOhm		[9] See PCB Declaration of Conformance PS119 for details.
Zero Balance		≤ 2 % FS	≤ 2 % FS	[2]	
Shunt Calibration		≤ 0.25 % FS	≤ 0.25 % FS	[3][2]	
Physical					SUPPLIED ACCESSORIES:
Size (Shaft Length x Housing Length x Housing Height)	3.23 in x 2.30 in x 2.00 in	82.0 mm x 58.4 mm x 50.8 mm		[7]	Model 7122R-04352A PRECISION CAL RESISTOR 43.575 kOhm
Weight	.75 lb	340 gm			OPTIONAL ACCESSORIES:
Mounting	1/4 inch Sq Drive	6.35 mm Sq Drive		[8]	Model 080920-01000 MODEL 920 PORTABLE DIGITAL INSTRUMENT
Sensing Element	Strain Gage	Strain Gage			Model 080962-01000 MODEL 962 DATA RECORDER
Housing Material	Aluminum	Aluminum			Model 097000-34149 INTERCONNECT CABLE
Shaft Material	Steel	Steel			Model 4242R-000600 MATING CONNECTOR PT06A-8-4S
Electrical Connector	PT02H-8-4P	PT02H-8-4P			
Maximum Speed	5000 RPM	5000 RPM			
		Entered: DMW			Engineer: JM
		Date: 3/14/2012			Date: 3/14/2012
		Sales: DM			Approved: PE
		Date: 3/14/2012			Spec Number:
		Date: 3/14/2012			51952
		PCB Load & Torque, Inc. 24350 Indoplex Circle Farmington Hills, MI 48335 UNITED STATES Phone: 866-684-7107 Fax: 716-684-0987 E-Mail: ltinfo@pcbloadtorque.com Web site: http://www.pcbloadtorque.com			
					

All specifications are at room temperature unless otherwise specified.
In the interest of constant product improvement, we reserve the right to change specifications without notice.