

Model Number 044-06		TWO CONDUCTOR, COIL CABLE		Revision: NR ECN #:	
Performance Number of Conductors Cable Style Cable Configuration Environmental Temperature Range Electrical Capacitance (conductor to conductor @ 70 °F (21 °C)) Physical Cable Jacket Diameter (± .010 in) Cable Jacket Material Cable Jacket Color Conductor Material Conductor Diameter (24 AWG) Insulation Material Over Conductor(s) Shield Type Over Conductor(s) Shield Material Over Conductor(s) Bend Radius (minimum) Weight		ENGLISH 2 Multi Conductor - Shielded Not Twisted -76 to +176 °F 20 pF/ft 0.17 in Polyurethane Black Tin Plated Copper 0.011 in Polypropylene Spiral : 90% Minimum Coverage Tinned Copper 1.7 in 0.20 lb [1]			
		SI 2 Multi Conductor - Shielded Not Twisted -60 to +80 °C 66 pF/m 4.32 mm Polyurethane Black Tin Plated Copper 0.279 mm Polypropylene Spiral : 90% Minimum Coverage Tinned Copper 43.2 mm 0.09 kg [1]			
Optional versions have identical specifications and accessories as listed for the standard model except where noted below. More than one option may be used.					
NOTES: [1] Typical.					
Entered: <i>Jet</i>		Engineer: <i>DAP</i>		Sales: <i>MFC</i>	
Date: <i>10/31/05</i>		Date: <i>10/31/05</i>		Date: <i>10/31/05</i>	
				Spec Number: 31945	
 IMI SENSORS A PCB PIEZOTRONICS DIV. IMI Sensors 3425 Walden Depew, NY 14043 Phone: 800-959-4464 Fax: 716-684-3823 E-Mail: imi@pcb.com					
All specifications are at room temperature unless otherwise specified. In the interest of constant product improvement, we reserve the right to change specifications without notice. ICP® is a registered trademark of PCB Group, Inc.					