

Model Number 062	3 CONDUCTOR TWISTED SHIELDED CABLE		Revision: NR ECN #:	
Performance	ENGLISH	SI	OPTIONAL VERSIONS	
Number of Conductors	3	3	Optional versions have identical specifications and accessories as listed for the standard model except where noted below. More than one option may be used.	
Cable Style	Multi Conductor - Shielded	Multi Conductor - Shielded		
Cable Configuration	Twisted Bundle	Twisted Bundle		
Environmental				
Temperature Range	-65 to +250 °F	-54 to +121 °C		
Electrical				
Impedance	73 ohm	73 ohm	[1]	
Capacitance (conductor to conductor @ 70 °F (21 °C))	20 pF/ft	66 pF/m		
Physical				
Cable Jacket Diameter (± .005 in)	0.160 in	4.06 mm	[1]	
Cable Jacket Material	Polyurethane	Polyurethane	NOTES:	
Cable Jacket Color	Black	Black	[1] Typical.	
Conductor Style	Stranded - 19 Strands 40 AWG	Stranded - 19 Strands 40 AWG		
Conductor Material	Tin Plated Copper	Tin Plated Copper		
Conductor Diameter (28 AWG)	0.013 in	0.330 mm	[1]	
Insulation Material Over Conductor(s)	FEP Teflon	FEP Teflon	Entered: <i>ZH</i>	
Shield Type Over Bundle	Braid: 94% Minimum Coverage	Braid: 94% Minimum Coverage	Engineer: <i>DM</i>	
Shield Material Over Bundle	Tin Plated Copper	Tin Plated Copper	Sales: <i>MFC</i>	
Filler Material	Synthetic FFP	Synthetic FFP	Approved: <i>MS</i>	
Bend Radius (minimum)	1.60 in	40.64 mm	Date: <i>10/21/05</i>	
Weight	0.28 oz/ft	26.04 gm/m	Date: <i>10/21/05</i>	
<i>All specifications are at room temperature unless otherwise specified.</i>			Date: <i>10/21/05</i>	
<i>In the interest of constant product improvement, we reserve the right to change specifications without notice.</i>			Date: <i>10/21/05</i>	
ICP® is a registered trademark of PCB Group, Inc.			Date: <i>10/21/05</i>	
			Date: <i>10/21/05</i>	
			Spec Number: 32062	
				
			IMI Sensors 3425 Walden Depew, NY 14043 Phone: 800-959-4464 Fax: 716-684-3823 E-Mail: imi@pcb.com	