

Model Number 105C22		ICP® PRESSURE SENSOR		Revision: H ECN #: 55250		
Performance		ENGLISH	SI	OPTIONAL VERSIONS		
Measurement Range(for ±5V output)		5,000 psi	34,475 kPa	Optional versions have identical specifications and accessories as listed for the standard model except where noted below. More than one option may be used. M - Metric Mount W - Water Resistant Cable		
Sensitivity(± 15 %)		1.0 mV/psi	0.145 mV/kPa			
Maximum Pressure		7,500 psi	51,700 kPa			
Resolution		0.1 psi	0.69 kPa			[1]
Resonant Frequency		≥ 250 kHz	≥ 250 kHz			
Rise Time		≤ 2 μ sec	≤ 2 μ sec			
Low Frequency Response(- 5 %)		0.5 Hz	0.5 Hz			
Non-Linearity		≤ 2 % FS	≤ 2 % FS			[2]
Environmental						
Acceleration Sensitivity		0.04 psi/g	0.028 kPa/(m/s ²)			[1]
Temperature Range(Operating)		-100 to +250 °F	-73 to +121 °C			
Temperature Coefficient of Sensitivity		≤ 0.09 %/°F	≤ 0.162 %/°C			
Maximum Flash Temperature		3,000 °F	1,649 °C			
Maximum Vibration		1,000 g pk	9,800 m/s ² pk			
Maximum Shock		5,000 g pk	49,000 m/s ² pk			
Electrical						
Output Polarity(Positive Pressure)		Positive	Positive			
Discharge Time Constant(at room temp)		≥ 1.0 sec	≥ 1.0 sec			
Excitation Voltage		22 to 30 VDC	22 to 30 VDC			
Constant Current Excitation		2 to 20 mA	2 to 20 mA			
Output Impedance		< 100 Ohm	< 100 Ohm			
Output Bias Voltage		8 to 14 VDC	8 to 14 VDC			
Physical						
Sensing Geometry		Compression	Compression			
Sensing Element		Quartz	Quartz			
Housing Material		Stainless Steel	Stainless Steel			
Diaphragm		17-4 Stainless Steel	17-4 Stainless Steel			
Sealing		Welded Hermetic	Welded Hermetic			
Electrical Connector		5-44 Coaxial	5-44 Coaxial			
Weight		0.055 oz	1.56 gm			
NOTES: [1]Typical. [2]Zero-based, least-squares, straight line method. [3]See PCB Declaration of Conformance PS023 for details.						
SUPPLIED ACCESSORIES: Model 018C10 Miniature coaxial cable, vinyl insulation jacket, 10-ft, 5-44 coaxial plug to BNC plug (1) Model 040A37 Hex nut driver (1) Model 065A10 Seal ring 0.138" OD x 0.101" ID x 0.022" thk brass (3) Model 065A38 Seal & Sleeve 0.138" OD x 0.101" ID x 0.105" thk, brass. (3) Model PCS-1 Calibration of dynamic pressure sensors at 100% full scale, max 15 kpsi range.						
Entered: ND		Engineer: RPF		Sales: RWM		
Date: 10/07/2024		Date: 10/07/2024		Date: 10/07/2024		
				Approved: RPF		
				Spec Number:		
				11322		
				Phone: 716-684-0001		
				Fax: 716-684-0987		
				E-Mail: info@pcb.com		
				AN AMPHENOL COMPANY		
				3425 Walden Avenue, Depew, NY 14043		

All specifications are at room temperature unless otherwise specified.
In the interest of constant product improvement, we reserve the right to change specifications without notice.
ICP® is a registered trademark of PCB Piezotronics, Inc.