

	ENGLISH	SI	
Performance			
Sensitivity(± 15 %)	6 pC/psi	0.870 pC/kPa	
Measurement Range	100 psi	690 kPa	
Maximum Pressure	3,000 psi	20,685 kPa	
Resonant Frequency	≥ 55 kHz	≥ 55 kHz	
Rise Time(Reflected)	≤ 9 μ sec	≤ 9 μ sec	
Non-Linearity	≤ 1 % FS	≤ 1 % FS	[1]
Environmental			
Maximum Shock	2,000 g pk	19,600 m/s ² pk	
Acceleration Sensitivity	0.029 psi/g	0.0204 kPa/(m/s ²)	[2]
Temperature Range(Operating)	-400 to 750 °F	-240 to 399 °C	[3]
Temperature Coefficient of Sensitivity	0.04 %/°F	0.072 %/°C	[2]
Maximum Flash Temperature	3,000 °F	1,649 °C	
Maximum Vibration	500 g pk	4,900 m/s ² pk	
Electrical			
Output Polarity(Positive Pressure)	Negative	Negative	
Capacitance	30 pF	30 pF	[2]
Insulation Resistance(at 600°F[315°C])	> 10 ⁹ Ohm	> 10 ⁹ Ohm	
Insulation Resistance(at 750°F[399°C])	> 10 ⁸ Ohm	> 10 ⁸ Ohm	
Insulation Resistance(at room temp)	> 10 ¹¹ Ohm	> 10 ¹¹ Ohm	
Physical			
Sensing Element	Quartz	Quartz	
Housing Material	316L Stainless Steel	316L Stainless Steel	
Diaphragm	316L Stainless Steel	316L Stainless Steel	
Sealing	Welded Hermetic	Welded Hermetic	
Electrical Connector	10-32 Coaxial Jack	10-32 Coaxial Jack	
Weight	.717 oz	20.3 gm	

OPTIONAL VERSIONS		
Optional versions have identical specifications and accessories as listed for the standard model except where noted below. More than one option may be used.		
E - Emralon coating		
Electrical Isolation	(Case) 10 ⁸ Ohm	(Case) 10 ⁸ Ohm
Coating	Emralon	Emralon
Temperature Range	-65 to 275 °F	-54 to 135 °C

NOTES:
 [1]Zero-based, least-squares, straight line method.
 [2]Typical.
 [3]When used with blocking capacitor and hardline cable.
 [4]See PCB Declaration of Conformance PS158 for details.

SUPPLIED ACCESSORIES:
 Model 060A12 Clamp nut, 9/16-18-2A thd, 9/16" hex (1)
 Model 060A14 Metric clamp nut, M14 x 1.25-6g thd, 14 mm hex, stainless steel (1)
 Model 065A37 Seal ring 0.497 OD x 0.437 ID x 0.025 thk Brass (3)
 Model PCS-1 Calibration of dynamic pressure sensors up to 100% range
 Model PCS-17 Electrostatic Actuator (ESA) frequency response from 20 Hz to 50 kHz
 Model PCS-24 Sensor sensitivity calibration with Pistonphone

Entered: ND	Engineer: AJA	Sales: RWM	Approved: AJA	Spec Number:
Date: 06/01/2026	Date: 06/01/2026	Date: 06/01/2026	Date: 06/01/2026	19272



All specifications are at room temperature unless otherwise specified.
 In the interest of constant product improvement, we reserve the right to change specifications without notice.
 ICP® is a registered trademark of PCB Piezotronics, Inc.

PCB PIEZOTRONICS
 AN AMPHENOL COMPANY
 Phone: 716-684-0001
 Fax: 716-684-0987
 E-Mail: info@pcb.com

3425 Walden Avenue, Depew, NY 14043