Model Number 121A45	ICP [®] PRESSURE SENSOR							evision: D CN #: 55309
Performance	ENGLISH	SI			OF	TIONAL VERSIO	NS	
Measurement Range(for ±5V output)	500 psi	3,447 kPa		Optional versions	have identical specific	ations and accessorie	es as listed for the st	andard model exc
		1.45 mV/kPa		•	where noted belo	ow. More than one of	otion may be used.	
Sensitivity(± 15 %)	10 mV/psi							
Maximum Pressure	8,000 psi	55,158 kPa	[4]					
Resolution	3 mpsi	0.02 kPa	[1]					
Resonant Frequency	≥ 60 kHz	≥ 60 kHz						
Rise Time(Reflected)	≤4µsec	≤ 4 µ sec						
Low Frequency Response(- 5 %)	0.5 Hz	0.5 Hz						
Non-Linearity	≤ 2.0 % FS	≤ 2.0 % FS	[2]					
Environmental		_						
Acceleration Sensitivity	0.025 psi/g	0.018 kPa/(m/s²)	[1]					
Temperature Range(Operating)	-65 to +250 °F	-54 to +121 ℃						
Hazardous Area Approval	See Manual	See Manual						
Electrical								
Output Polarity(Positive Pressure)	Positive	Positive						
Discharge Time Constant(at room temp)	≥ 1.0 sec	≥ 1.0 sec						
Excitation Voltage	22 to 28 VDC	22 to 28 VDC						
Constant Current Excitation	2 to 20 mA	2 to 20 mA						
Output Impedance	< 100 Ohm	< 100 Ohm						
Output Bias Voltage	8 to 14 VDC	8 to 14 VDC						
Electrical Isolation								
	≥ 10 ⁸ Ohm	≥ 10 ⁸ Ohm						
Physical								
Sensing Geometry	Compression	Compression						
Sensing Element	Quartz	Quartz						
Housing Material	316L Stainless Steel	316L Stainless Steel						
Diaphragm	316L Stainless Steel	316L Stainless Steel						
Sealing	Welded Hermetic	Welded Hermetic						
Electrical Connector	2-Pin MIL-C-5015	2-Pin MIL-C-5015						
Weight	2.7 oz	75.6 gm						
<i>с с</i>				[3]See PCB Decla	ast-squares, straight l ration of Conformanc CESSORIES: rration of dynamic pre	e PS059 for details.	% full scale, max 15	xpsi range.
				Entered: ND	Engineer: RPF	Sales: DPC	Approved: RPF	Spec Number:
				Date: 10/25/2024	Date: 10/25/2024	Date: 10/25/2024	Date: 10/25/2024	38074
All specifications are at room temperature u In the interest of constant product improven ICP [®] is a registered trademark of PCB Piezo	nent, we reserve the right to ch	ange specifications without	t notice.	_	TIEZOTROI AN AMPHENOL (Jule, Depew, NY 14043	E-Mail: i	716-684-0001 -684-0987 nfo@pcb.com	-