

Performance	ENGLISH	SI
Channels	8	8
Sensor Input Type(s)	ICP®, Voltage, Charge	ICP®, Voltage, Charge
Gain(ICP®/ Voltage Input)	0.1 to 200	0.1 to 200
Gain(mV/pC)(Charge Input)	0.01 to 2000	0.01 to 2000
Gain Increment(minimum)(ICP®/ Voltage Input)	0.1	0.1
Gain Increment(minimum)(Charge Input)	0.01	0.01
Accuracy(ICP®/ Voltage Input)(Gain, 0.1 to 0.4)	± 5 %	± 5 %
Accuracy(ICP®/ Voltage Input)(Gain, 0.5 to 200)	± 1 %	± 1 %
Accuracy(Charge Input)(Gain, 0.01 to 0.04)	± 6 %	± 6 %
Accuracy(Charge Input)(Gain, 0.05 to 2000)	± 1 %	± 1 %
Input Range(maximum)(Charge Input)	100,000 pC pk	100,000 pC pk
Input Range(maximum)(ICP® Input)	10 Vpk	10 Vpk
Input Range(maximum)(Voltage Input)	± 5 Vpk	± 5 Vpk
Low Frequency Response(-5 %)(ICP®/ Voltage Input)	≤ 0.05 Hz	≤ 0.05 Hz
Low Frequency Response(-5 %)(Charge Input)	0.5 Hz	0.5 Hz
Electrical Filter Roll-off	160 dB/decade	160 dB/decade
Filter Type(8-pole Butterworth)	Low Pass	Low Pass
High Frequency Response(-5%)(Gain from 0.01 to 99.9)	>100 kHz	>100 kHz
High Frequency Response(-5%)(Gain from 100 to 2000)	>50 kHz	>50 kHz
Electrical Filter Corner Frequency(-10 %)	0.1-0.3-1-3-10-30 kHz	0.1-0.3-1-3-10-30 kHz
Electrical Filter Pass Band Amplitude Accuracy	1 %	1 %
Phase Response(at 1 kHz)	± 2 °	± 2 °
Non-Linearity	1 %	1 %
Cross Talk	<-72 dB	<-72 dB
TEDS Sensor Support	Yes	Yes
Fault/Bias Monitor LEDs	Open/Short/Overload	Open/Short/Overload
Control Interface		
Digital Control Interface	Ethernet	Ethernet
Human Interface	Keypad	Keypad
Display	2 rows, 16 columns	2 rows, 16 columns
Environmental		
Temperature Range(Operating)	+32 to +120 °F	0 to +50 °C
Electrical		
Power Required(direct input to unit)	AC Power	AC Power
AC Power(47 to 63 Hz)	100 to 240 VAC	100 to 240 VAC
AC Power	≤ 0.7 Amps	≤ 0.7 Amps
Excitation Voltage(To Sensor)	>24 VDC	>24 VDC
DC Offset	<50 mV	<50 mV
Constant Current Excitation(To Sensor)	2 to 20 mA	2 to 20 mA
Output Voltage(minimum)	10 V	10 V
Output Current(minimum)	10 mA	10 mA
Output Impedance	<50 Ohm	<50 Ohm
Broadband Electrical Noise(1 to 10,000 Hz)(Gain x1)	50 µV/rms	50 µV/rms
Spectral Noise(1 Hz)	8 µV/√Hz	8 µV/√Hz
Spectral Noise(10 Hz)	2 µV/√Hz	2 µV/√Hz
Spectral Noise(100 Hz)	0.7 µV/√Hz	0.7 µV/√Hz
Spectral Noise(1 kHz)	0.7 µV/√Hz	0.7 µV/√Hz
Spectral Noise(10 kHz)	0.6 µV/√Hz	0.6 µV/√Hz
Broadband Electrical Noise(1 to 10,000 Hz)(Gain x10)	75 µV rms	75 µV rms
Spectral Noise(1 Hz)	18 µV/√Hz	18 µV/√Hz
Spectral Noise(10 Hz)	1.5 µV/√Hz	1.5 µV/√Hz
Spectral Noise(100 Hz)	1.0 µV/√Hz	1.0 µV/√Hz
Spectral Noise(1 kHz)	1.0 µV/√Hz	1.0 µV/√Hz
Spectral Noise(10 kHz)	1.0 µV/√Hz	1.0 µV/√Hz
Broadband Electrical Noise(1 to 10,000 Hz)(Gain x100)	350 µV rms	350 µV rms
Spectral Noise(1 Hz)	100 µV/√Hz	100 µV/√Hz
Spectral Noise(10 Hz)	10 µV/√Hz	10 µV/√Hz
Spectral Noise(100 Hz)	6 µV/√Hz	6 µV/√Hz
Spectral Noise(1 kHz)	5 µV/√Hz	5 µV/√Hz
Broadband Electrical Noise(1 to 10,000 Hz)(0.1 mV/pC)	52.0 µV/rms	52.0 µV/rms
Spectral Noise(10 kHz)	5 µV/√Hz	5 µV/√Hz
Spectral Noise(1 Hz)	10.0 µV/√Hz	10.0 µV/√Hz
Spectral Noise(10 Hz)	1.5 µV/√Hz	1.5 µV/√Hz
Spectral Noise(100 Hz)	0.6 µV/√Hz	0.6 µV/√Hz
Spectral Noise(1 kHz)	0.6 µV/√Hz	0.6 µV/√Hz
Spectral Noise(10 kHz)	0.6 µV/√Hz	0.6 µV/√Hz
Broadband Electrical Noise(1 to 10,000 Hz)(1.0 mV/pC)	52.0 µV/rms	52.0 µV/rms
Spectral Noise(1 Hz)	14.0 µV/√Hz	14.0 µV/√Hz
Spectral Noise(10 Hz)	2.0 µV/√Hz	2.0 µV/√Hz
Spectral Noise(100 Hz)	0.7 µV/√Hz	0.7 µV/√Hz
Spectral Noise(1 kHz)	0.7 µV/√Hz	0.7 µV/√Hz
Spectral Noise(10 kHz)	0.7 µV/√Hz	0.7 µV/√Hz
Broadband Electrical Noise(1 to 10,000 Hz)(10.0 mV/pC)	56.0 µV/rms	56.0 µV/rms
Spectral Noise(1 Hz)	15.0 µV/√Hz	15.0 µV/√Hz
Spectral Noise(10 Hz)	2.0 µV/√Hz	2.0 µV/√Hz
Spectral Noise(100 Hz)	0.6 µV/√Hz	0.6 µV/√Hz
Spectral Noise(1 kHz)	0.6 µV/√Hz	0.6 µV/√Hz
Spectral Noise(10 kHz)	0.6 µV/√Hz	0.6 µV/√Hz
Oscillator(+/- 2%)(Internal Generator - ICP®/ Voltage Mode)	0.1 V pk	0.1 V pk
Oscillator(+/- 2%)(Internal Generator - Charge Mode)	100 pC pk	100 pC pk
Oscillator(+/- 2%)	100/1000 Hz	100/1000 Hz
Overload Threshold(± 0.5 Vpk)	± 10 Vpk	± 10 Vpk
Physical		
Electrical Connector(Input, sensor)	BNC Jack	BNC Jack
Electrical Connector(Output)	BNC Jack	BNC Jack
Electrical Connector(Ethernet)	RJ-45	RJ-45
Size (Height x Width x Depth)(nominal)	1.75 in x 19 in x 13.7 in	44.5 mm x 482.6 mm x 348 mm
Weight	8 lb	3.6 kg


OPTIONAL VERSIONS

Optional versions have identical specifications and accessories as listed for the standard model except where noted below. More than one option may be used.


NOTES:

[1] Use T1.6A fuse.
 [2] User adjustable, factory set at 4 mA (± 1.0 mA). Each channel individually adjustable.
 [3] Typical.
 [4] Max input signal is dependant on sensor bias.
 [5] The low frequency tolerance is accurate within ±25% of the specified frequency.
 [6] The high frequency tolerance is accurate within ±5% of the specified frequency.
 [7] See PCB Declaration of Conformance PS024 for details.

SUPPLIED ACCESSORIES:				
Model 017AXX Power Cord (1)				
Model EE75 PCB MCSC Control Software. (1)				
Entered: ND	Engineer: CPH	Sales: AH	Approved: JWH	Spec Number:
Date: 12/3/2025	Date: 12/3/2025	Date: 12/3/2025	Date: 12/3/2025	46951



All specifications are at room temperature unless otherwise specified.
 In the interest of constant product improvement, we reserve the right to change specifications without notice.
 ICP® is a registered trademark of PCB Group, Inc.



Phone: 716-684-0001
 Fax: 716-684-0987
 E-Mail: info@pcb.com

3425 Walden Avenue, Depew, NY 14043