


Model Number 488B04	POWER SUPPLY			Revision: A ECN #: 32528
Environmental	ENGLISH	SI	OPTIONAL VERSIONS	
Temperature Range(Operating)	32 to 104 °F	0 to 40 °C	Optional versions have identical specifications and accessories as listed for the standard model except where noted below. More than one option may be used.	
Humidity Range(Non-Condensing)	0 to 95 %	0 to 95 %	488B04/NC - Does not include a 017AXX Power Cord	
Electrical			NOTES:	
Output Voltage	32 - 38 VDC	32 - 38 VDC	[1] See PCB Declaration of Conformance PS024 for details.	
Output Current	0.54 amps	0.54 amps	SUPPLIED ACCESSORIES:	
AC Power(50 to 60 Hz)	100 to 240 VAC	100 to 240 VAC	Model 017AXX Power Cord (1)	
(50 to 60 Hz)	0.6 amps	0.6 amps	Entered: <i>JH</i> Engineer: <i>PH</i> Sales: <i>gjm</i> Approved: <i>EB</i> Spec Number:	
AC Ripple(Peak to Peak)	<350 mV	<350 mV	Date: <i>3-15-10</i> Date: <i>3-3-10</i> Date: <i>2-26-10</i> Date: <i>3-9-10</i> 45177	
Physical			PCB PIEZOTRONICS ELECTRONICS DIVISION 3425 Walden Avenue, Depew, NY 14043 Phone: 716-684-0001 Fax: 716-684-0987 E-Mail: electronics@pcb.com	
Electrical Connector(AC Power Input)	IEC 320	IEC 320		
(Output DC)	DIN 5 Pin (Male)	DIN 5 Pin (Male)		
Size (Height x Width x Depth)	1.3 in x 2.13 in x 3.76 in	33 mm x 54.1 mm x 95.5 mm		
Weight	1.25 lb	0.57 kg		
	[1]			
<i>All specifications are at room temperature unless otherwise specified. In the interest of constant product improvement, we reserve the right to change specifications without notice.</i>				
ICP® is a registered trademark of PCB Group, Inc.				