

#### Model 66212ANZ1

## **ICP® TO-5 Accelerometer**

## **Installation and Operating Manual**

For assistance with the operation of this product, contact PCB Piezotronics, Inc.

Toll-free: 800-959-4464 24-hour SensorLine: 716-684-0001

Fax: 716-684-3823 E-mail: imi@pcb.com Web: www.imi-sensors.com







Warranty, Service, Repair, and Return Policies and Instructions

The information contained in this document supersedes all similar information that may be found elsewhere in this manual.

**Total Customer Satisfaction** – PCB Piezotronics guarantees Total Customer Satisfaction. If, at any time, for any reason, you are not completely satisfied with any PCB product, PCB will repair, replace, or exchange it at no charge. You may also choose to have your purchase price refunded in lieu of the repair, replacement, or exchange of the product.

**Service** – Due to the sophisticated nature of the sensors and associated instrumentation provided by Piezotronics, user servicing or repair is not recommended and, if attempted, may void the factory warranty. Routine maintenance, such as the cleaning of electrical connectors, housings, and mounting surfaces with solutions and techniques that will not harm the physical material of construction, is acceptable. Caution should be observed to insure that liquids are not permitted to migrate into devices that are not hermetically sealed. Such devices should only be wiped with a dampened cloth and never submerged or have liquids poured upon them.

Repair – In the event that equipment becomes damaged or ceases to operate, arrangements should be made to return the equipment to PCB Piezotronics for repair. User servicing or repair is not recommended and, if attempted, may void the factory warranty.

Calibration - Routine calibration of sensors and associated instrumentation is recommended as this helps build confidence in measurement accuracy and acquired Equipment data. calibration cycles are typically established by the users own quality regimen. When in doubt about a calibration cycle, a good "rule of thumb" is to recalibrate on an annual basis. It is also good practice to recalibrate after exposure to any severe temperature shock, extreme. load. or other environmental influence, or prior to any critical test.

PCB Piezotronics maintains an ISO-9001 certified metrology laboratory and offers calibration services, which are accredited by A2LA to ISO/IEC 17025. with full traceability to SI through N.I.S.T. In addition to the normally supplied calibration, special testing is also available, such as: sensitivity at elevated or cryogenic temperatures, phase response, extended high or low frequency response, extended range, leak testing, hydrostatic pressure testing, and others. For information on standard recalibration services special testing, contact your local PCB Piezotronics distributor, sales representative. or factory customer service representative.

**Returning Equipment** – Following these procedures will insure that your returned materials are handled in the most expedient manner. Before

equipment to PCB returning any Piezotronics, local contact your distributor, sales representative, or factory customer service representative to obtain a Return Warranty, Service, Repair, and Return Policies and **Instructions** Materials Authorization (RMA) Number. This RMA number should be clearly marked on the outside of all package(s) and on the packing list(s) accompanying the shipment. A detailed account of the nature of the problem(s) being experienced with the equipment should also be included inside the package(s) containing any returned materials.

A Purchase Order, included with the returned materials, will expedite the turn-around of serviced equipment. It is recommended to include authorization on the Purchase Order for PCB to proceed with any repairs, as long as they do not exceed 50% of the replacement cost of the returned item(s). PCB will provide a price quotation or replacement recommendation for any item whose repair costs would exceed 50% of replacement cost, or any item that is not economically feasible to repair. For routine calibration services. the include Purchase Order should authorization to proceed and return at current pricing, which can be obtained a factory customer service from representative.

**Warranty** – All equipment and repair services provided by PCB Piezotronics, Inc. are covered by a limited warranty against defective material and workmanship for a period of one year from date of original purchase. Contact

PCB for a complete statement of our warranty. Expendable items, such as batteries and mounting hardware, are not covered by warranty. Mechanical damage to equipment due to improper use is not covered by warranty. Electronic circuitry failure caused by the introduction of unregulated or improper excitation power or electrostatic discharge is not covered by warranty.

Contact Information - International customers should direct all inquiries to their local distributor or sales office. A complete list of distributors and offices found be at www.pcb.com. Customers within the United States may contact their local sales representative factory customer representative. A complete list of sales can be representatives found www.pcb.com. Toll-free telephone numbers for a factory customer service representative. in the responsible for this product, can be found on the title page at the front of this manual. Our ship to address and general contact numbers are:

PCB Piezotronics, Inc. 3425 Walden Ave. Depew, NY14043 USA Toll-free: (800) 828-8840

24-hour SensorLine<sup>SM</sup>: (716) 684-0001

Website: www.pcb.com E-mail: info@pcb.com



## PCB工业监视和测量设备 - 中国RoHS2公布表

PCB Industrial Monitoring and Measuring Equipment - China RoHS 2 Disclosure Table

	有害物质							
部件名称	铅 (Pb)	汞 (Hg)	镉 (Cd)	六价铬 (Cr(VI))	<b>多溴</b> 联苯 (PBB)	多溴二苯醚 (PBDE)		
住房	0	0	0	0	0	0		
PCB板	X	0	0	0	0	0		
电气连接器	0	0	0	0	0	0		
压电晶 <b>体</b>	Х	0	0	0	0	0		
环 <b>氧</b>	0	0	0	0	0	0		
铁氟龙	0	0	0	0	0	0		
电子	0	0	0	0	0	0		
厚膜基板	0	0	Х	0	0	0		
电线	0	0	0	0	0	0		
电缆	Х	0	0	0	0	0		
塑料	0	0	0	0	0	0		
焊接	Х	0	0	0	0	0		
铜合金/黄铜	Х	0	0	0	0	0		

## 本表格依据 SJ/T 11364 的规定编制。

#### CHINA RoHS COMPLIANCE

O:表示该有害物质在该部件所有均质材料中的含量均在 GB/T 26572 规定的限量要求以下。

X:表示该有害物质至少在该部件的某一均质材料中的含量超出 GB/T 26572 规定的限量要求。 铅是欧洲RoHS指令2011/65/ EU附件三和附件四目前由于允许的豁免。

Component Name	Hazardous Substances							
	Lead (Pb)	Mercury (Hg)	Cadmium (Cd)	Chromium VI Compounds (Cr(VI))	Polybrominated Biphenyls (PBB)	Polybrominated Diphenyl Ethers (PBDE)		
Housing	0	0	0	0	0	0		
PCB Board	Х	0	0	0	0	0		
Electrical Connectors	0	0	0	0	0	0		
Piezoelectric Crystals	Х	0	0	0	0	0		
Ероху	0	0	0	0	0	0		
Teflon	0	0	0	0	0	0		
Electronics	0	0	0	0	0	0		
Thick Film Substrate	0	0	Х	0	0	0		
Wires	0	0	0	0	0	0		
Cables	Х	0	0	0	0	0		
Plastic	0	0	0	0	0	0		
Solder	Х	0	0	0	0	0		
Copper Alloy/Brass	Х	0	0	0	0	0		

This table is prepared in accordance with the provisions of SJ/T 11364.

DOCUMENT NUMBER: 21354 DOCUMENT REVISION: C

ECN: 45605

O: Indicates that said hazardous substance contained in all of the homogeneous materials for this part is below the limit requirement of GB/T 26572.

X: Indicates that said hazardous substance contained in at least one of the homogeneous materials for this part is above the limit requirement of GB/T 26572.

Lead is present due to allowed exemption in Annex III or Annex IV of the European RoHS Directive 2011/65/EU.

Model Number 66212ANZ1

# ICP® TO-5 ACCELEROMETER

Revision: A ECN #: 35587

ENGLISH	SI	-
100 mV/g	1.02 mV/(m/s²)	[2]
± 50 g	± 490 m/s <sup>2</sup>	[3]
30 to 60,000 cpm	0.5 to 10,000 Hz	[4][5]
	25 kHz	[1][5]
	3434 um/sec <sup>2</sup> rms	[1]
≤ 1 %	≤ 1 %	[6]
≤ 7 %	≤ 7 %	
5000 g pk	49,000 m/s <sup>2</sup> pk	
-65 to +185 °F	-54 to +85 °C	
See Graph	See Graph	[1]
	0000000000000000000000000000000000000	-
≤ 2 sec	≤ 2 sec	
0.3 sec	0.3 sec	
18 to 28 VDC	18 to 28 VDC	
2 to 20 mA	2 to 20 mA	
<150 ohm	<150 ohm	
8 to 12 VDC	8 to 12 VDC	
8 μg/√Hz	78.5 (µm/sec <sup>2</sup> )/√Hz	[1]
5 μg/√Hz		[1]
4 μg/√Hz		[1]
5. FOCO MA 1980	1012 (p1111000 )/ 1112	
0.36 in x 0.38 in	9.1 mm x 9.7 mm	
0.1 oz		
Adhesive/Solder		
Ceramic	Ceramic	
Shear	Shear	
Stainless Steel	Stainless Steel	
Welded Hermetic	Welded Hermetic	
Header Pins	Header Pins	
Bottom	Bottom	
Signal / Power	Signal / Power	
Ground	Ground	
Not Used	Not Used	
Typical Sensitivity  6 3 0 0 -3 -6	Deviation vs Temperature	
	± 50 g  30 to 60,000 cpm 1500 kcpm 350 µg rms ≤ 1 % ≤ 7 %  5000 g pk -65 to +185 °F See Graph  ≤ 2 sec 0.3 sec 18 to 28 VDC 2 to 20 mA <150 ohm 8 to 12 VDC 8 µg/√Hz 5 µg/√Hz 4 µg/√Hz 0.36 in x 0.38 in 0.1 oz Adhesive/Solder Ceramic Shear Stainless Steel Welded Hermetic Header Pins Bottom Signal / Power Ground Not Used	± 50 g  30 to 60,000 cpm 1500 kcpm 25 kHz 350 µg rms 3434 µm/sec² rms ≤ 1 % ≤ 7 %  5000 g pk -65 to +185 °F See Graph  ≤ 2 sec 0.3 sec 18 to 28 VDC 2 to 20 mA <150 ohm 8 to 12 VDC 8 µg/\Hz 5 µg/\Hz 4 µg/\Hz 5 µg/\Hz 4 µg/\Hz 4 µg/\Hz 5 µg/\Hz 4 µg/\Hz 5 µg/\Hz 4 µg/\Hz 5 µg/\Hz 5 µg/\Hz 4 µg/\Hz 5 µg/\Hz 5 µg/\Hz 5 µg/\Hz 6 in x 0.38 in 0.1 oz Adhesive/Solder Ceramic Shear Stainless Steel Welded Hermetic Header Pins Bottom Signal / Power Ground Not Used  150 to 10,000 Hz 25 kHz 3434 µm/sec² 7ms  ≤ 2 kHz 4 9,000 m/s² pk -54 to +85 °C See Graph  49,000 m/s² pk -54 to +85 °C See Graph  49,000 m/s² pk -54 to +85 °C See Graph  49,000 m/s² pk -54 to +85 °C See Graph  5 to 20 mA <150 ohm 8 to 12 VDC 8 µg/\Hz 4 p1 (µm/sec²)/\Hz 4 9.1 (µm/sec²)/\Hz 4 9.1 (µm/sec²)/\Hz 5 µg/\Hz 5 µg/\Hz 6 Signal / Power Signal / Power Ground Not Used  5 to 12 VDC 8 µg/\Hz 6 Namical Signal / Power Ground Not Used

#### **OPTIONAL VERSIONS**

Optional versions have identical specifications and accessories as listed for the standard model except where noted below. More than one option may be used.

HT - High temperature, extends normal operation temperatures

Temperature Range(Operating)

-65 to 250 °F -54 to +121 °C

RH - RoHS Compliant

#### NOTES:

[1] Typical.
[2] Conversion Factor 1g = 9.81 m/s².
[3] Negative output in upward direction when pin mounted.
[4] The high frequency tolerance is accurate within ±10% of the specified frequency.
[5] Performance depends on mounting

- [6] Zero-based, least-squares, straight line method.
  [7] See PCB Declaration of Conformance PS023 or PS060 for details.

[7] -75-50-25 0 25 50 75 100125150175200225

Temperature (°F)

All specifications are at room temperature unless otherwise specified. In the interest of constant product improvement, we reserve the right to change specifications without notice.

ICP® is a registered trademark of PCB Group, Inc.

SUPPLIED ACCESSORIES:

Model ICS-2 NIST-traceable single-axis single-point amplitude response calibration at 6000 cpm (100 Hz) (1)

Entered: mu Sales: Approved: por Engineer: 😙 Spec Number: Date: 1 Date: 🛕 Date:11 Date: 46761



Phone: 800-959-4464 Fax: 716-684-3823 E-Mail: imi@pcb.com