| Model Number<br><b>691A50/08</b>  | BNC TERMINATION ENCLOSURE  |                                       |  |   |                      |  | Revision: A<br>ECN #: 47548 |      |
|---|--|---------------------------------------|--|---|----------------------|--|-----------------------------|------|
| Performance   | ENGLISH  8 OPTIONA 8 Optional versions have identical specifications |                                       |  |   |                      | ONS  |                             |      |
| Channels Environmental  | 8  | 8                                     | Optional versions have identical specifications and accessories as listed for the standard model except where noted below. More than one option may be used. |   |                      |  |                             |      |
| Enclosure Rating  | Nema 4X  | IP66                                  |  |   |                      |  |                             |      |
| Temperature Range   | -15 to +158 °F   | -26 to +70 °C                         | PS - Painted Steel   |   |                      |  |                             | [2]  |
| Physical  |  |                                       | Enclosure Rating   |   | IF                   | P65 N  | ema 12                      |      |
| Electrical Connector(Input)   | Terminal Block   | Terminal Block                        | Weight   |   | 5.                   | 0 lb   | 2.3 kg                      |      |
| Electrical Connector(Output)  | BNC Jack   | BNC Jack                              |  |   |                      |  |                             |      |
| Cable Input   | PGME07   | PGME07                                | SS - Stainless Steel Enclosure   |   |                      |  |                             | [2]  |
| Housing Material  | Fiberglass   | Fiberglass                            | Enclosure Rating   |   | IF                   | P66 N  | ema 4X                      |      |
| Size (Height x Width x Depth)   | 8 in x 6 in x 4 in   | 203 mm x 152 mm x 102 mm              | Weight   |   | 5.                   | 5 lb   | 2.5 kg                      |      |
| Weight C C  | 2.5 lb   | 1.14 kg                               |  | claration of Conform                            | nance PS174 for deta | ails.  |                             |      |
| All specifications are at room tempera<br>In the interest of constant product imp |  | change specifications without notice. | Entered: LK  | Engineer: BAM                                   | Sales: MC            | Approved: BAM                                    | Spec Nur                    | mher |
| ICP® is a registered trademark of PCB Group, Inc.                                 |  | Entered. Ert                          | Engineer. Britis   | oales. Me                                       | пррточеа. Влич       | Орестии  | mber.                       |      |
|   |  |                                       | Date: 12/4/2017  | Date: 12/4/2017                                 | Date: 12/4/2017      | Date: 12/4/2017                                  | 2065                        | 57   |
|   |  |                                       |  | 5ENSORS<br>EOTRONICS DIV.<br>enue, Depew, NY 14 |                      | Phone: 800-95<br>Fax: 716-684-3<br>E-Mail: imi@p | 823                         |      |