

PERFORMANCE SPECIFICATION
 ACCELEROMETER
 (773-XXX-Y-ZZZ)
 RoHS COMPLIANT

Document Number	Rev	Date	Entered by	Description of Change	Change Accountable Engineer	ECO
77025	A	12/8/23	NAD	Initial Release of Performance Specification of 773 Models	HX	53327

1.0 DESCRIPTION

The ENDEVCO® Model 773 is a Tri-axial low g DC Accelerometer that utilizes unique variable capacitance microsensors. This Accelerometer is designed for measurement of relatively low level accelerations in automotive ride quality, motorsports and high speed rail applications where measurement of whole body motion immediately after the accelerometer is subjected to a shock motion and in the presence of severe vibrational inputs is required. 773 meet the requirements for IP67.

The 773 Accelerometer is available with a choice of two power options. One option (U) allows for operation from 7V to 36V. The second option (R) allows for operation at a regulated excitation voltage of 5V. The Accelerometer features various full scale g ranges including $\pm 5g$, $\pm 10g$, $\pm 30g$, $\pm 50g$, $\pm 100g$, $\pm 200g$, and provides single-ended output with a 2.5V output bias voltage.

2.0 ELECTRICAL CHARACTERISTICS

All specifications assume +75°F (+24°C), +5 Vdc excitation (for 773-XXX-R-ZZZ) or +15 Vdc excitation (for 773-XXX-U-ZZZ) unless otherwise stated. The following parameters are 100% tested.

	<u>Units</u>	<u>Range Dash Number</u>					
RANGE	g	<u>-5</u>	<u>-10</u>	<u>-30</u>	<u>-50</u>	<u>-100</u>	<u>-200</u>
2.1 SENSITIVITY	mV/g	400 ± 20	200 ± 10	66 ± 4	40 ± 2	20 ± 1.0	10 ± 1.0
2.2 FREQUENCY RESPONSE ($\pm 5\%$, ref 100 Hz) typical	Hz	0-200	0-750	0-750	0-750	0-1000	0-1000
FREQUENCY RESPONSE ($\pm 1dB$, ref 100 Hz) max	Hz	0-300	0-1500	0-2000	0-2000	0-2000	0-2000
REQUENCY RESPONSE ($\pm 3dB$, ref 100 Hz) typical	Hz	0-550	0-2500	0-2800	0-2800	0-5000	0-5000
2.3 ZERO MEASURAND OUTPUT	mV	2500 ± 75	2500 ± 75	2500 ± 75	2500 ± 75	2500 ± 75	2500 ± 75

3.0 TYPICAL PERFORMANCE

The following parameters are established from testing of sample units.

3.1 TRANSVERSE SENSITIVITY (Typical)	%	3.0	3.0	3.0	3.0	3.0	3.0
-----------------------------------------	---	-----	-----	-----	-----	-----	-----

		<u>Units</u>	<u>Range Dash Number</u>					
			<u>-2</u>	<u>-10</u>	<u>-30</u>	<u>-50</u>	<u>-100</u>	<u>-200</u>
3.2	THERMAL ZERO SHIFT (MAX) -40°C to +100°C, ref. 24°C (-40°F to +212°F, ref. 75°F)	%FSO [1]	±2.0	±2.0	±2.0	±2.0	±2.0	±2.0
3.3	THERMAL SENS SHIFT (MAX) -40°C to +100°C, ref. 24°C (-40°F to +212°F, ref. 75°F)	%	±2.0	±2.0	±2.0	±2.0	±2.0	±2.0
3.4	COMBINED NON-LINEARITY (BFSL) AND HYSTERESIS (Typical)	%FSO	±0.5	±0.5	±0.5	±0.5	±0.5	±0.5
3.5	NATURAL FREQUENCY, TYP	Hz	1700	2700	5500	5500	9800	9800
3.6	THRESHOLD (RESOLUTION) [2]	equiv. g's.	0.0005	.001	.003	.005	.01	.02
3.7	WARM-UP TIME (to within 1% of final output value)					30 ms		
4.0	<u>ELECTRICAL</u>							
4.1	EXCITATION VOLTAGE For option "R" supply voltage For option "U" supply voltage					5 Vdc 7 to 36 Vdc		
4.2	CURRENT DRAIN					8mA max each axis, 24 mA max total		
4.3	OUTPUT IMPEDANCE					100 ohms max		
4.4	LOAD					10K ohms resistance minimum 50 pF capacitance maximum		
4.5	RESIDUAL NOISE					50 µVrms typ, 100 µVrms max; 0.5 to 100 Hz 500 µVrms typ, 1.0 mVrms max; 0.5Hz to 10 kHz		
4.6	MAXIMUM EXCITATION VOLTAGE WITHOUT DAMAGE For option "R" supply voltage For option "U" supply voltage					7 Vdc 45 Vdc		
4.7	INPUT VOLTAGE PROTECTION					REVERSE POLARITY PROTECTED (For "U" option only)		
4.8	INSULATION RESISTANCE Case to leads shorted together Shield to leads shorted together					100 Meg Ohms minimum at 50 Vdc		

5.0	<u>PHYSICAL</u>	
5.1	WEIGHT (typical)	24 grams (without cable) plus cable at 20 grams/meter
5.2	CASE MATERIAL	Anodized aluminum alloy.
5.2.1	CABLE TYPE	Integral 10 conductor, # 28 AWG PVC insulated leads, Shielded with black PVC jacket.
5.3	MOUNTING/TORQUE	Mounting 2x #4 or M3 Screws, 6 lb-in (0.7 N-m)
6.0	<u>ENVIRONMENTAL</u>	
6.1	ACCELERATION LIMITS (in any direction)	
6.1.1	Vibration	20 g rms random 20-2000 Hz
6.1.2	Shock	10000g (0.15 mS haversine pulse)
6.2	TEMPERATURE	
6.2.1	Operating Range	-40°F to +212°F (-40°C to +100°C)
6.2.2	Storage Range	-40°F to +212°F (-40°C to +100°C)
6.3	Humidity	IP67
7.0	<u>CALIBRATION DATA</u>	
7.1	SENSITIVITY	Measured at 1g and 100 Hz for the -5 Measured at 10 g and 100Hz for the -10, -30 -50, -100 and -200
7.2	FREQUENCY RESPONSE	Measured at 1g, 20 to 1000 Hz for the -5 Measured at 10 g, 20 to 10000 Hz for the -10 -30, -50,-100 and -200
7.3	ZERO MEASURAND OUTPUT	Measured at room temperature
8.0	<u>ACCESSORIES</u>	
	2X #4-40 (1" length) Socket Head Cap Screw (EH864) and Washer (EHW289)	

9.0 **NOTES**

[1] Full scale output (FSO) is nominally 4 volts

[2] THRESHOLD = [2X MAX. RESIDUAL NOISE; .5 TO 100Hz] SENSITIVITY

[3] Model Number Definition:

