

PCB Piezotronics Inc. claims proprietary rights in the information disclosed hereon. Neither it nor any reproduction thereof will be disclosed to others without the written consent of PCB Piezotronics Inc.

REVISIONS

REV	DESCRIPTION	DIN
NR	RELEASED TO DRAFTING	53548

77413

Ø.021 [.53] SAFETY WIRE HOLES

Ø.140 [Ø3.56] THRU

Ø.600 [Ø15.24]

UNIT IDENTIFICATION

.24 [6.1] .363 [9.22]

INSULATED MOUNTING SCREW ASSEMBLY 6-32 UNC - 2A THREAD

MATES WITH ENDEVCO 3000 SERIES CABLES WITH 10-32 UNF - 2A CONNECTOR

.21 [5.3]

.51 [13.0]

.35 [8.8]

.013 [.33]

.152 [3.86] .088 [2.24]

INSULATED MOUNTING SURFACE (HARD ANODIZED ALUMINUM)

Ø.495 [Ø12.57]

UNLESS OTHERWISE SPECIFIED TOLERANCES ARE:

DRAWN		CHECKED		ENGINEER	
NJF	02/14/23	JDM	02/14/23	DAM	02/14/23



PCB PIEZOTRONICS OF NC, INC (DBA ENDEVCO) 10869 NC HIGHWAY 903, HALIFAX, NC 27839

DIMENSIONS IN INCHES	
DECIMALS	XX ±.03
	XXX ±.010
ANGLES	± 2 DEGREES

DIMENSIONS IN MILLIMETERS [IN BRACKETS]	
DECIMALS	X ± 0.8
	XX ± 0.25
ANGLES	± 2 DEGREES

CABLE TOLERANCES IN ENGLISH	
1" ≤ LENGTH < 1'	= +1"/ - 0
1' ≤ LENGTH < 5'	= +2"/ - 0
5' ≤ LENGTH < 100'	= +6"/ - 0
100' ≤ LENGTH	= +1' / - 0

CABLE TOLERANCES IN METRIC	
2.54cm ≤ LENGTH < 30.5cm	= +2.54cm / - 0
30.5cm ≤ LENGTH < 1.5m	= +5.1cm / - 0
1.5m ≤ LENGTH < 30.5m	= +15.2cm / - 0
30.5m ≤ LENGTH	= +30.5cm / - 0

FILLETS AND RADII	
.003 - .005	

FILLETS AND RADII	
0.07 - 0.13	

TITLE OUTLINE DRAWING 2221F SERIES

CODE IDENT. NO. 8DN13	DWG. NO. 77413
-----------------------	----------------

SCALE: 4X	SHEET 1 OF 1
-----------	--------------