

	ENGLISH	SI
Performance		
Connector Style	Coaxial	Coaxial
Connection Type	Plug (male pin)	Plug (male pin)
Coupling Method	Threaded	Threaded
Coupling Thread	10-32 female	10-32 female
Strain Relief	Molded Boot	Molded Boot
Environmental		
Temperature Range	-76 to 450 °F	-60 to 232 °C
Physical		
ROHS Compliant	Yes	Yes
Housing Material	Brass	Brass
Mounting Torque	15 to 20 in-oz	10.6 to 14.1 N-cm
Size (OD x Hex x Length)	.29 in x .25 in x .93 in	7.4 mm x 6.4 mm x 23.6 mm
Weight	.06 oz	1.6 gm

OPTIONAL VERSIONS

Optional versions have identical specifications and accessories as listed for the standard model except where noted below. More than one option may be used.

NOTES:

Entered: ND	Engineer: MB	Sales: BS	Approved: BAM	Spec Number:
Date: 12/07/2022	Date: 12/07/2022	Date: 12/07/2022	Date: 12/07/2022	32027

All specifications are at room temperature unless otherwise specified.
 In the interest of constant product improvement, we reserve the right to change specifications without notice.
 ICP® is a registered trademark of PCB Piezotronics, Inc.

PCB PIEZOTRONICS
 AN AMPHENOL COMPANY

Phone: 716-684-0001
 Fax: 716-684-0987
 E-Mail: info@pcb.com

3425 Walden Avenue, Depew, NY 14043