Model Number AP	CABLE CONNECTOR				
Performance	ENGLISH	SI			
Connector Style	MIL-C-5015	MIL-C-5015	Optional versi		
Connector Style	Multi-conductor	Multi-conductor			
Connection Type	2-socket	2-socket			
Connection Type	Jack (female socket / recepticle)	Jack (female socket / recepticle)			
Coupling Method	Threaded	Threaded			
Coupling Thread	5/8-24 female	5/8-24 female			
Strain Relief	Clamp	Clamp			
Environmental	·	•			
Temperature Range	-320 to +257 °F	-196 to +125 °C	Entered: LK		
Physical	V	V			
ROHS Compliant	Yes	Yes	Date: 2/27/201		
Size (OD x Length)	0.87 in x 1.78 in	22 mm x 45.21 mm			
Weight All specifications are at room	1.19 oz om temperature unless otherwise specified.	33.87 gm			
	product improvement, we reserve the right to	change specifications without notice.			
ICP® is a registered trader	nark of PCB Group, Inc.		6		

OPTIONAL VERSIONS

Optional versions have identical specifications and accessories as listed for the standard model except where noted below. More than one option may be used.

Entered: LK	Engineer: KW	Sales: MC	Approved: BAM	Spec Number:
Date: 2/27/2019	Date: 2/27/2019	Date: 2/27/2019	Date: 2/27/2019	32473



IMI Sensors 3425 Walden Depew, NY 14043 UNITED STATES Phone: 800-959-4464 Fax: 716-684-3823

E-Mail: imi@pcb.com

Web site: http://www.imi-sensors.com

Revision: B

ECN #: 48813