

Model Number AY	CABLE CONNECTOR			Revision: D ECN #: 56383										
Performance	ENGLISH	SI		OPTIONAL VERSIONS										
Connector Style	Multi-conductor	Multi-conductor		Optional versions have identical specifications and accessories as listed for the standard model except where noted below. More than one option may be used.										
Connection Type	4-socket	4-socket												
Connection Type	Plug with Female Contact	Plug with Female Contact												
Coupling Method	Threaded	Threaded												
Coupling Thread	1/4-28 female	1/4-28 female												
Strain Relief	Molded Boot	Molded Boot												
Environmental														
Temperature Range	-320 to 325 °F	-195 to 162.7 °C												
Physical														
ROHS Compliant	Yes	Yes												
Housing Material	Brass	Brass												
Size (OD x Length)	.30 in x 1.0 in	7.6 mm x 25 mm												
Weight	.11 oz	3.0 gm	[1]											
NOTES:														
[1]Typical.														
<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 20%;">Entered: ND</td> <td style="width: 20%;">Engineer: MJN</td> <td style="width: 20%;">Sales: BS</td> <td style="width: 20%;">Approved: BAM</td> <td style="width: 20%;">Spec Number:</td> </tr> <tr> <td>Date: 01/12/2026</td> <td>Date: 01/12/2026</td> <td>Date: 01/12/2026</td> <td>Date: 01/12/2026</td> <td>32040</td> </tr> </table>					Entered: ND	Engineer: MJN	Sales: BS	Approved: BAM	Spec Number:	Date: 01/12/2026	Date: 01/12/2026	Date: 01/12/2026	Date: 01/12/2026	32040
Entered: ND	Engineer: MJN	Sales: BS	Approved: BAM	Spec Number:										
Date: 01/12/2026	Date: 01/12/2026	Date: 01/12/2026	Date: 01/12/2026	32040										
 PCB PIEZOTRONICS AN AMPHENOL COMPANY														
Phone: 716-684-0001 Fax: 716-684-0987 E-Mail: info@pcb.com														
3425 Walden Avenue, Depew, NY 14043														
All specifications are at room temperature unless otherwise specified. In the interest of constant product improvement, we reserve the right to change specifications without notice. ICP® is a registered trademark of PCB Piezotronics, Inc.														