Model Number BP	CABLE CONNECTOR						sion: B I #: 48970
Performance Connector Style Connection Type Connection Type Coupling Method Coupling Thread Strain Relief Environmental	ENGLISH MIL-C-5015 Multi-conductor 2-socket Jack (female socket / recepticle) Threaded 5/8-24 female Clamp	SI MIL-C-5015 Multi-conductor 2-socket Jack (female socket / recepticle) Threaded 5/8-24 female Clamp	OPTIONAL VERSIONS Optional versions have identical specifications and accessories as listed for the standard mode except where noted below. More than one option may be used.				
Temperature Range Physical	-320 to +325 °F	-196 to +163 °C	Entered: LK	Engineer: NJF	Sales: MC	Approved: NJF	Spec Number:
ROHS Compliant Size (OD x Length) Weight	Yes 0.87 in x 1.78 in 1.19 oz	Yes 22 mm x 45.21 mm 33.87 gm	Date: 12/14/2018	Date: 12/14/2018	Date: 12/14/2018	Date: 12/14/2018	32477
All specifications are at room temperature unless otherwise specified. In the interest of constant product improvement, we reserve the right to change specifications without notice. ICP [®] is a registered trademark of PCB Group, Inc.			**PCB PIEZOTRONICS** 3425 Walden Avenue, Depew, NY 14043			Phone: 716-684-0001 Fax: 716-684-0987 E-Mail: info@pcb.com	