| Model Number<br>CF   | CABLE CONNECTOR                       |   |                                       |                     |   | Revision NR<br>ECN #            |            |  |
|--|---------------------------------------|---|---------------------------------------|---------------------|---|---------------------------------|------------|--|
| CF Performance Connector Style Connector Style Connection Type Coupling Method Coupling Thread Strain Relief Environmental Temperature Range Physical Size (OD x Length) Weight All specifications are at room tempe | nprovement, we reserve the right to c | SI<br>MIL-C-5015<br>Multi-conductor<br>2-socket<br>Jack (female socket /<br>recepticle)<br>Threaded<br>5/8-24 female<br>Clamp<br>-55 to +121 °C<br>21.08 mm x 61.98<br>mm<br>12.40 gm | Optional Version<br>for standard mode |                     | ns have identical spe<br>ted below. More that   | ECN #:<br>ecifications and acce |            |  |
|  |                                       |   | Entered: DMP                          | Engineer:<br>MFG    | Sales: NJF  |                                 | Spec Numbe |  |
|  |                                       |   | Date:<br>11/28/2005                   | Date:<br>11/28/2005 | Date:<br>11/28/2005   |                                 | 32474      |  |
|  |                                       |   | A POB PIEZOTRONICS DIM.               |                     | y: IMI Sensors<br>3425 Walden<br>Depew, NY 14043<br>UNITED STATES<br>300-959-4464<br>Cod 2020 | 1                               |            |  |