DATA COLLECTOR CONNECTOR		
ENGLISH	SI	Optional Version
D-Sub	D-Sub	for standard mo
25-pin	25-pin	
Molded Boot	Molded Boot	
-67 to +221 °F	-55 to +105 °C	
2.33 in x 1.48 in x	59.18 mm x 37.59	
0.59 in	mm x 14.99 mm	
1.12 oz	31.63 gm	
	ENGLISH D-Sub 25-pin Molded Boot -67 to +221 °F 2.33 in x 1.48 in x 0.59 in	ENGLISH SI D-Sub D-Sub 25-pin 25-pin Molded Boot Molded Boot  -67 to +221 °F -55 to +105 °C  2.33 in x 1.48 in x 59.18 mm x 37.59 0.59 in mm x 14.99 mm

Optional Versions (Optional versions have identical specifications and accessories as listed for standard model except where noted below. More than one option maybe used.)

Revision NR

All specifications are at room temperature unless otherwise specified. In the interest of constant product improvement, we reserve the right to change specifications without notice.

ICP® is a registered trademark of PCB group, Inc.

Entered: DMP	Engineer: MFG		Spec Number:
Date: 12/13/2005	Date: 12/13/2005		32593



Company: IMI Sensors Address: 3425 Walden Depew, NY 14043 UNITED STATES

Phone: 800-959-4464 Fax: 716-684-3823 E-mail: imi@pcb.com

Web site: http://www.imi-sensors.com