Model Number DS	CABLE CONNECTOR			
Performance	ENGLISH	SI	Optio	
Connector Style	MIL-C-5015	MIL-C-5015	for sta	
Connector Style	Multi-conductor	Multi-conductor		
Connection Type	3-socket	3-socket		
Connection Type	Jack (female	Jack (female socket /		
	socket / recepticle)	recepticle)		
Coupling Method (Keyed)	Push On	Push On		
Strain Relief	Molded Boot	Molded Boot		
Environmental				
Temperature Range	-67 to +250 °F	-55 to +121 °C		
Physical				
ROHS Compliant	No	No		
Housing Material	Silicone	Silicone		
Size (OD x Length)	0.88 in x 2.4 in	22 mm x 61 mm		
Weight	0.88 oz	25 gm		

ECN #: 33775 **Optional Versions** (Optional versions have identical specifications and accessories as listed for standard model except where noted below. More than one option maybe used.)

Revision NR

All specifications are at room temperature unless otherwise specified.

In the interest of constant product improvement, we reserve the right to change specifications without notice.

ICP® is a registered trademark of PCB group, Inc.

Entered: do		Spec Number:
Date: 08/11/2010		47470
08/11/2010		



Company: IMI Sensors Address: 3425 Walden Depew, NY 14043 UNITED STATES

Phone: 800-959-4464 Fax: 716-684-3823 E-mail: imi@pcb.com Web site: http://www.imi-sensors.com