

Model Name

EX600B13

Revision: E

ECN #: 56707

Performance

Sensitivity(± 5 %)

Measurement Range(Peak)

Frequency Range(± 5 %)

Frequency Range(± 10 %)

Resonant Frequency

Broadband Resolution(1 to 10,000 Hz)

Non-Linearity

Transverse Sensitivity

Environmental

Overload Limit(Shock)

Temperature Range(Accelerometer)

Temperature Range(Charge Amplifier)

Temperature Response

Base Strain Sensitivity

Electrical

Settling Time(at 70 °F within 1% of bias)

Discharge Time Constant

Excitation Voltage

Constant Current Excitation

Output Impedance

Output Bias Voltage

Spectral Noise(10 Hz)

Spectral Noise(100 Hz)

Spectral Noise(1 kHz)

Electrical Isolation

Physical

Size (Diameter x Height)

Weight(with cable)

Mounting

Sensing Element

Sensing Geometry

Housing Material

Sealing

Electrical Connector

Electrical Connection Position

Cable Length

Cable Type

ENGLISH

100.0 mV/g

± 50 g

282 to 210,000 cpm

204 to 300,000 cpm

1,200 kcpm

450 µg

± 1 %

< 5 %

1,000 g pk

-65 to +900 °F

-60 to +250 °F

See Graph

≤ 0.006 g/µε

≤ 1.0 sec

≥ .10 sec

22 to 28 VDC

2.2 to 20 mA

< 1,000 Ohm

12 to 16 VDC

30 µg/√Hz

8 µg/√Hz

4 µg/√Hz

> 10⁸ Ohm

1.5 in x 0.75 in

10.5 oz

Through Holes (3)

UHT-12™

Shear

Inconel

Welded Hermetic

2-Pin MIL-C-5015

Side

10 ft

Integral Hardline Cable

SI

10.2 mV/(m/s²)

± 490 m/s²

4.7 to 3,500 Hz

3.4 to 5,000 Hz

20 kHz

4,415 µm/sec²

± 1 %

< 5 %

9,810 m/s² pk

-54 to +482 °C

-51 to +121 °C

See Graph

≤ 0.06 (m/s²)/µε

≤ 1.0 sec

≥ .10 sec

22 to 28 VDC

2.2 to 20 mA

< 1,000 Ohm

12 to 16 VDC

294 (µm/sec²)/√Hz

78 (µm/sec²)/√Hz

39 (µm/sec²)/√Hz

> 10⁸ Ohm

38.1 mm x 19.1 mm

300 gm

Through Holes (3)

UHT-12™

Shear

Inconel

Welded Hermetic

2-Pin MIL-C-5015

Side

3 m

Integral Hardline Cable

[1]

[2][3]

[4]

[4][1]

[5]

[1]

[4]

[1]

[4][1]

[4][1]

[4][1]

OPTIONAL VERSIONS

Optional versions have identical specifications and accessories as listed for the standard model except where noted below. More than one option may be used.

NOTES:

[1]Conversion Factor 1g = 9.81 m/s².

[2]1Hz = 60 cpm (cycles per minute).

[3]The high frequency tolerance is accurate within ±10% of the specified frequency.

[4]Typical value.

[5]Zero-based, least-squares, straight line method.

[6]See PCB Declaration of Conformance PS116 for details.

[7]See Model's "Instructions For Use" (IFU) for North American Conformity and Certification Statements.

SUPPLIED ACCESSORIES:

Model 081A99 Cap Screw (3)

Model ICS-1 NIST-traceable single-axis amplitude response calibration from 600 cpm (10 Hz) to upper 5% frequency (1)

Entered: ND

Engineer: gs

Sales: JL

Approved: BAM

Spec Number:

Date: 06/29/2026

Date: 06/29/2026

Date: 06/29/2026

Date: 06/29/2026

44818

CE

UK

CA

[6]

Ex

ETL

Intertek

[7]

IMI SENSORS

A PCB PIEZOTRONICS DIV.

3425 Walden Avenue, Depew, NY 14043

Phone: 800-959-4464

Fax: 716-684-3823

E-Mail: imi@pcb.com

All specifications are at room temperature unless otherwise specified.

In the interest of constant product improvement, we reserve the right to change specifications without notice.

ICP® is a registered trademark of PCB Piezotronics, Inc.