


| Model Number FY | CABLE CONNECTOR | | Revision NR ECN #: | | |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------|----------------------------|
| Performance Connector Style Connector Style Connection Type Strain Relief Environmental Temperature Range Physical Size (OD x Length) Weight | ENGLISH MIL-C-5015 Multi-conductor 3-socket Molded Boot -67 to +250 °F 0.88 in x 2.62 in 1.75 oz | SI MIL-C-5015 Multi-conductor 3-socket Molded Boot -55 to +121 °C 22 mm x 66.55 mm 49.70 gm | Optional Versions (Optional versions have identical specifications and accessories as listed for standard model except where noted below. More than one option maybe used.) | | |
| <p><i>All specifications are at room temperature unless otherwise specified.</i></p> <p>In the interest of constant product improvement, we reserve the right to change specifications without notice.</p> <p>ICP® is a registered trademark of PCB group, Inc.</p> | | | | | |
| Entered: Date: | | Engineer: Date: | Sales: Date: | Approved: Date: | Spec Number: N/A |
|  | | Company: IMI Sensors Address: 3425 Walden Depew, NY 14043 UNITED STATES Phone: 800-959-4464 Fax: 716-684-3823 E-mail: imi@pcb.com Web site: http://www.imi-sensors.com | | | |