


Model Number GW	CABLE CONNECTOR		Revision A ECN #: 26254	
Performance Connector Style Connection Type Strain Relief	ENGLISH LEMO 4-pin Molded Boot	SI LEMO 4-pin Molded Boot	Optional Versions (Optional versions have identical specifications and accessories as listed for standard model except where noted below. More than one option maybe used.)	
Environmental Temperature Range Maximum Shock Vibration Survivability	-40 to 176 °F 100 g pk 15 g pk	-40 to 80 °C 981 m/s ² pk 147 m/s ² pk		
Physical Electrical Connections (Pin 1) Electrical Connections (Pin 2) Electrical Connections (Pin 3) Electrical Connections (Pin 4) Electrical Connections (Shell) Housing Material	Z axis Y axis X axis Ground No Connection Brass	Z axis Y axis X axis Ground No Connection Brass		
<p><i>All specifications are at room temperature unless otherwise specified.</i></p> <p>In the interest of constant product improvement, we reserve the right to change specifications without notice.</p> <p>ICP® is a registered trademark of PCB group, Inc.</p>				
Entered: do		Engineer: WDC	Sales: BAM	Spec Number:
Date: 04/12/2007		Date: 04/12/2007	Date: 04/12/2007	37192
				3425 Walden Avenue Depew, NY 14043 UNITED STATES Phone: 800-828-8840 Fax: 716-684-0987 E-mail: info@pcb.com Web site: www.pcb.com

