Model Number HR	CABLE CONNECTOR		
Performance	<u>ENGLISH</u>	<u>SI</u>	
Connector Style	SMB	SMB	Optional vers
Connector Style	Coaxial	Coaxial	i i
Connection Type	Plug with Female Contact	Plug with Female Contact	
Coupling Method	Push On	Push On	CT - Cable T
Strain Relief	Heat Shrink	Heat Shrink	
Environmental			
Temperature Range	-67 to 275 °F	-55 to 135 °C	
Electrical			
Impedance	50 Ohm	50 Ohm	
Insulation Resistance	1 GOhm	1 GOhm	Entered: LK
Physical			
ROHS Compliant	Yes	Yes	Date: 1/16/201
Housing Material	Brass	Brass	
Size (Length x Height x Width)	.60 in x .54 in x .25	15.3 mm x 13.7 mm x 6.4	_
Weight	0.14 oz	3.8 gm	
All specifications are at room temperat	ure unless otherwise specified.	-	WPL
In the interest of constant product impr	ovement, we reserve the right to change	e specifications without notice.	3425 Walden

OPTIONAL VERSIONS

Il versions have identical specifications and accessories as listed for the standard model except where noted below. More than one option may be used.

able Type

Entered: LK	Engineer: KW	Sales: AT	Approved: BAM	Spec Number:
Date: 1/16/2019	Date: 1/16/2019	Date: 1/16/2019	Date: 1/16/2019	70810



Phone: 716-684-0001 Fax: 716-684-0987 E-Mail: info@pcb.com

Revision: NR

ECN #: 48998