Model Number JX	CABLE CONNECTOR			Revision: NR ECN #:
Performance Connector Style Connector Style Connection Type Coupling Method Strain Relief Environmental	ENGLISH Triple Splice BNC Jack (female socket / recepticle) Bayonet Molded Boot	SI Triple Splice BNC Jack (female socket / recepticle) Bayonet Molded Boot	OPTIONAL VERSIONS Optional versions have identical specifications and accessories as except where noted below. More than one option	listed for the standard model may be used.
Temperature Range Physical	-67 to 230 °F	-55 to 110 °C		
Electrical Connections	X axis	X axis	Entered: THEngineer: UTN Sales: Ahm Approv	Spec Number:
Electrical Connections	Y axis	Y axis	Engineer: UTN Sales: Approv	Spec Number:
Electrical Connections	Z axis	Z axis	Date: 9-8-08 Date: 9/5/08 Date: 9/5/08 Date:	9/5/08 41063
ROHS Compliant	No	No	7 0 0 0 000 75763 1546.	11/08 41003
Size (Length)	12 in	30.5 cm	**	
All specifications are at room temperature unless otherwise specified. In the interest of constant product improvement, we reserve the right to change specifications without notice.			Fax: 7	e: 716-684-0001 16-684-0987 l: electronics@pcb.com