

Model Number JZ	<h1>CABLE CONNECTOR</h1>			Revision: A ECN #: 37525																																														
<table border="0"> <tr> <td>Performance</td> <td style="text-align: center;">ENGLISH</td> <td style="text-align: center;">SI</td> </tr> <tr> <td>Connector Style</td> <td>Triple Splice</td> <td>Triple Splice</td> </tr> <tr> <td>Connector Style</td> <td>Coaxial</td> <td>Coaxial</td> </tr> <tr> <td>Connection Type</td> <td>Jack (female socket / receptacle)</td> <td>Jack (female socket / receptacle)</td> </tr> <tr> <td>Coupling Method</td> <td>Threaded</td> <td>Threaded</td> </tr> <tr> <td>Coupling Thread</td> <td>10-32 male</td> <td>10-32 male</td> </tr> <tr> <td>Strain Relief</td> <td>Molded Boot</td> <td>Molded Boot</td> </tr> <tr> <td>Environmental</td> <td></td> <td></td> </tr> <tr> <td>Temperature Range</td> <td>-15 to 400 °F</td> <td>-26 to 204 °C</td> </tr> <tr> <td>Physical</td> <td></td> <td></td> </tr> <tr> <td>Electrical Connections</td> <td>X axis</td> <td>X axis</td> </tr> <tr> <td>Electrical Connections</td> <td>Y axis</td> <td>Y axis</td> </tr> <tr> <td>Electrical Connections</td> <td>Z axis</td> <td>Z axis</td> </tr> <tr> <td>ROHS Compliant</td> <td>No</td> <td>No</td> </tr> <tr> <td>Size (Length)</td> <td>12 in</td> <td>30.5 cm</td> </tr> </table> <p><i>All specifications are at room temperature unless otherwise specified. In the interest of constant product improvement, we reserve the right to change specifications without notice.</i></p>			Performance	ENGLISH	SI	Connector Style	Triple Splice	Triple Splice	Connector Style	Coaxial	Coaxial	Connection Type	Jack (female socket / receptacle)	Jack (female socket / receptacle)	Coupling Method	Threaded	Threaded	Coupling Thread	10-32 male	10-32 male	Strain Relief	Molded Boot	Molded Boot	Environmental			Temperature Range	-15 to 400 °F	-26 to 204 °C	Physical			Electrical Connections	X axis	X axis	Electrical Connections	Y axis	Y axis	Electrical Connections	Z axis	Z axis	ROHS Compliant	No	No	Size (Length)	12 in	30.5 cm	<p style="text-align: center;">OPTIONAL VERSIONS</p> <p>Optional versions have identical specifications and accessories as listed for the standard model except where noted below. More than one option may be used.</p>		
Performance	ENGLISH	SI																																																
Connector Style	Triple Splice	Triple Splice																																																
Connector Style	Coaxial	Coaxial																																																
Connection Type	Jack (female socket / receptacle)	Jack (female socket / receptacle)																																																
Coupling Method	Threaded	Threaded																																																
Coupling Thread	10-32 male	10-32 male																																																
Strain Relief	Molded Boot	Molded Boot																																																
Environmental																																																		
Temperature Range	-15 to 400 °F	-26 to 204 °C																																																
Physical																																																		
Electrical Connections	X axis	X axis																																																
Electrical Connections	Y axis	Y axis																																																
Electrical Connections	Z axis	Z axis																																																
ROHS Compliant	No	No																																																
Size (Length)	12 in	30.5 cm																																																
			<table border="1" style="width: 100%; text-align: center;"> <tr> <td>Entered: DMW</td> <td>Engineer: JDK</td> <td>Sales: JJM</td> <td>Approved: APB</td> <td>Spec Number:</td> </tr> <tr> <td>Date: 11/11/2011</td> <td>Date: 11/11/2011</td> <td>Date: 11/11/2011</td> <td>Date: 11/11/2011</td> <td>41146</td> </tr> </table>			Entered: DMW	Engineer: JDK	Sales: JJM	Approved: APB	Spec Number:	Date: 11/11/2011	Date: 11/11/2011	Date: 11/11/2011	Date: 11/11/2011	41146																																			
Entered: DMW	Engineer: JDK	Sales: JJM	Approved: APB	Spec Number:																																														
Date: 11/11/2011	Date: 11/11/2011	Date: 11/11/2011	Date: 11/11/2011	41146																																														
			<div style="display: flex; justify-content: space-between; align-items: center;"> <div data-bbox="1119 560 1575 667">  <p>3425 Walden Avenue, Depew, NY 14043</p> </div> <div data-bbox="1575 560 1929 667"> <p> Phone: 716-684-0001 Fax: 716-684-0987 E-Mail: electronics@pcb.com </p> </div> </div>																																															