


Model Number LD	<b>CABLE CONNECTOR</b>			Revision: NR ECN #:	
<b>Performance</b> Connector Style Connector Style Connection Type Coupling Method Strain Relief <b>Environmental</b> Temperature Range <b>Physical</b> Electrical Connections Electrical Connections Electrical Connections ROHS Compliant Size (Length)	<b>ENGLISH</b> Triple Splice SMB Jack with Male Contact Snap-on Heat Shrink -67 to 230 °F X axis Y axis Z axis No 12 in	<b>SI</b> Triple Splice SMB Jack with Male Contact Snap-on Heat Shrink -55 to 110 °C X axis Y axis Z axis No 30.5 cm	<b>OPTIONAL VERSIONS</b> Optional versions have identical specifications and accessories as listed for the standard model except where noted below. More than one option may be used.		
			Entered: <i>BLS</i>	Engineer: <i>MJW</i>	Sales: <i>Jgm</i>
			Date: <i>9/3/08</i>	Date: <i>8/29/08</i>	Date: <i>8/29/08</i>
			Approved: <i>[Signature]</i>		Spec Number: <b>41022</b>
<i>All specifications are at room temperature unless otherwise specified.  In the interest of constant product improvement, we reserve the right to change specifications without notice.</i>			 <b>PCB PIEZOTRONICS</b> ELECTRONICS DIVISION 3425 Walden Avenue, Depew, NY 14043 Phone: 716-684-0001 Fax: 716-684-0987 E-Mail: <a href="mailto:electronics@pcb.com">electronics@pcb.com</a>		