Model Number <b>LK</b>		CABLE CON	NECTOR Revision: NR ECN #:
Performance Connector Style Connection Type Coupling Method Coupling Thread Strain Relief Environmental Temperature Range	ENGLISH Triple Splice SMA Plug (male pin) Threaded 1/4-36 female Heat Shrink	SI Triple Splice SMA Plug (male pin) Threaded 1/4-36 female Heat Shrink	OPTIONAL VERSIONS Optional versions have identical specifications and accessories as listed for the standard model except where noted below. More than one option may be used.
Physical Electrical Connections Electrical Connections Electrical Connections	X axis Y axis Z axis	X axis Y axis Z axis	Entered: Let Engineer: UJN Sales: JM Approved: MLH Spec Number:  Date: 1-9 0 9 Date: 1/9/09 Date: 1/9 0 9 Date: 1/9 0 9 41995
ROHS Compliant No No No Size (Length) 12 in 30.5 mm  All specifications are at room temperature unless otherwise specified. In the interest of constant product improvement, we reserve the right to change specifications without notice.		30.5 mm	Phone: 716-684-0001 Fax: 716-684-0987 Selectrionics Division 3425 Walden Avenue, Depew, NY 14043  Phone: 716-684-0901 Fax: 716-684-0987 E-Mail: electronics@pcb.com