

Model Number LV	CABLE CONNECTOR		Revision: NR ECN #:	
Performance	ENGLISH	SI	OPTIONAL VERSIONS	
Connector Style	Circular	Circular	Optional versions have identical specifications and accessories as listed for the standard model except where noted below. More than one option may be used.	
Connection Type	Breakaway 3-socket Jack (female socket / receptacle)	Breakaway 3-socket Jack (female socket / receptacle)		
Coupling Method	Snap-on	Snap-on		
Strain Relief	Potted	Potted		
Environmental			NOTES:	
Temperature Range	-40 to +176 °F	-40 to +80 °C	[1] Typical.	
Electrical				
Insulation Resistance	10 Gohm	10 Gohm		
Physical				
ROHS Compliant	No	No	Entered: JH Engineer: MHN Sales: MRS Approved: EB Spec Number:	
Housing Material	Plastic	Plastic	Date: 7-29-09 Date: 7-22-09 Date: 7-27-09 Date: 7-27-09 43638	
Size (OD x Length)	0.75 in x 2.2 in	19 mm x 57 mm		
Weight	0.39 oz	11.1 gm		
<p><i>All specifications are at room temperature unless otherwise specified. In the interest of constant product improvement, we reserve the right to change specifications without notice.</i></p>			<p>IMI SENSORS 3425 Walden Depew, NY 14043 UNITED STATES Phone: 800-959-4464 Fax: 716-684-3823 E-Mail: imi@pcb.com Web site: http://www.imi-sensors.com</p>	