Model Number NE	CABLE CONNECTOR			
Performance Connector Style Connection Type Coupling Method Strain Relief Environmental Temperature Range Electrical	ENGLISH LEMO Coaxial Plug (male pin) Push On Molded Boot -67 to +300 °F	SI LEMO Coaxial Plug (male pin) Push On Molded Boot		OPTIONAL VERSIONS Optional versions have identical specifications and accessories as listed for the standard model except where noted below. More than one option may be used.
Impedance Insulation Resistance Physical	50 ohm >10 Tohm	50 ohm >10 Tohm		NOTES: [1] Typical value.
Electrical Connections(Center Pin) (Shell) Housing Material Finish	Signal/Power Ground Brass Nickel Plated	Signal/Power Ground Brass Nickel Plated		Entered It Engineer: DORT Sales: IM Approved: BAM Spec Number: Date: I-21-12 Date: I-17-12 Date: I-17-12 Date: I-23-12 50868
Size (OD x Length) 0.252 in x 1.319 in 6.4 mm x 33.5 Weight 0.15 oz 4.2 g All specifications are at room temperature unless otherwise specified. In the interest of constant product improvement, we reserve the right to change specifications without notice.			[1]	Phone: 716-684-0001 Fax: 716-684-0987 ELECTRONICS DIVISION 3425 Walden Avenue, Depew, NY 14043 Phone: 716-684-0901 Fax: 716-684-0987 E-Mail: electronics@pcb.com