

	<u>ENGLISH</u>	<u>SI</u>
<b>Performance</b>		
Connector Style	Coaxial	Coaxial
Connection Type	Plug (male pin)	Plug (male pin)
Coupling Method	Threaded	Threaded
Coupling Thread	10-32 female	10-32 female
Strain Relief	Heat Shrink	Heat Shrink
<b>Environmental</b>		
Temperature Range	-320 to 250 °F	-196 to 121 °C
<b>Physical</b>		
ROHS Compliant	No	No
Size (OD x Length)	0.25 in x 0.94 in	6.4 mm x 24 mm
Weight	0.1 oz	2 gm

**OPTIONAL VERSIONS**

Optional versions have identical specifications and accessories as listed for the standard model except where noted below. More than one option may be used.

Entered: <i>yomw</i>	Engineer: <i>CPM</i>	Sales: <i>JJM</i>	Approved: <i>BPM</i>	Spec Number:
Date: <i>11/24/10</i>	Date: <i>11/24/10</i>	Date: <i>11/24/10</i>	Date: <i>11/24/10</i>	<b>48592</b>

*All specifications are at room temperature unless otherwise specified.  
In the interest of constant product improvement, we reserve the right to change specifications without notice.*

ICP® is a registered trademark of PCB Group, Inc.

 <p><b>PCB PIEZOTRONICS™</b> ELECTRONICS DIVISION 3425 Walden Avenue, Depew, NY 14043</p>	<p>Phone: 716-684-0001 Fax: 716-684-0987 E-Mail: <a href="mailto:electronics@pcb.com">electronics@pcb.com</a></p>
--	---