Model Number N V	CABLE CONNECTOR						evision: A CN #: 51731
Performance Connector Style Connector Style Connection Type Coupling Method Coupling Thread Strain Relief Environmental Temperature Range Physical Electrical Connections(Re Electrical Connections(We Electrical Connections(Bla Electrical Connections(Bla Electrical Connections(Sha) E	Threa 10-32 f Molder -67 to d) Xa Illow) Ya nite) Za nck) Gro	Splice uxial ale pin) ale pin) Ale pin) Ale pin) Ale pin) Ale pin Ale	Triple Splice Coaxial lug (male pin) Threaded 10-32 female Molded Boot -55 to 110 °C X axis Y axis Z axis Ground Ground/Shield Yes 30.5 cm	Optional versions have identical specific where noted belo	PTION AL VERSION S ations and accessories as ow. More than one option	s listed for the stands and the stands are stands and the stands are stands a	andard model except
				NOTES:			
				Entered: ND Engineer: GD		proved: BAM	Spec Number:
				Date: 05/13/2021 Date: 05/13/2021	Date: 05/13/2021 Dat	te: 05/13/2021	49967
All specifications are at ro	om temperature unless otherwise product improvement, we reserve	e specified. e the right to change spe	**PCB PIEZOTRONC5*** Phone: 716-684-0001 Fax: 716-684-0987 E-Mail: info@pcb.com				