

Model Number NX	CABLE CONNECTOR				Revision: NR ECN #: 35646
Performance	ENGLISH	SI	OPTIONAL VERSIONS		
Connector Style	Circular	Circular	Optional versions have identical specifications and accessories as listed for the standard model except where noted below. More than one option may be used.		
Connection Type	Plug with Female Contact	Plug with Female Contact			
Connection Type	4-socket	4-socket			
Coupling Method	Threaded	Threaded			
Coupling Thread	1/2 DS Female	1/2 DS Female			
Strain Relief	Clamp	Clamp			
Environmental					
Temperature Range	-40 to 250 °F	-40 to 121 °C			
Physical					
Electrical Connections(Socket A)	Pos (+) Signal	Pos (+) Signal			
Electrical Connections(Socket B)	Pos (+) Power	Pos (+) Power			
Electrical Connections(Socket C)	Ground	Ground			
Electrical Connections(Socket D)	Shield	Shield			
ROHS Compliant	No	No			
Finish	Chromate over Cadmium	Chromate over Cadmium			
Size (OD x Length)	.729 in x 1.91 in	18.5 mm x 48.5 mm			
Weight	.67 oz	19 gm			
<i>All specifications are at room temperature unless otherwise specified. In the interest of constant product improvement, we reserve the right to change specifications without notice.</i>					
ICP® is a registered trademark of PCB Group, Inc.					

Entered: DMW	Engineer: JDK	Sales: JJM	Approved: BAM	Spec Number:
Date: 4/27/2011	Date: 4/27/2011	Date: 4/27/2011	Date: 4/27/2011	49839



PCB PIEZOTRONICS
ELECTRONICS DIVISION

Phone: 716-684-0001
Fax: 716-684-0987
E-Mail: electronics@pcb.com

3425 Walden Avenue, Depew, NY 14043