Model Number PC	CABLE CONNECTOR					Revision: A ECN #: 38253
Performance Connector Style  Connection Type Coupling Method Strain Relief Environmental Temperature Range		ENGLISH LEMO Triple Splice Plug (male pin) Push On Molded Boot -67 to +300 °F	<u>SI</u> LEMO Triple Splice Plug (male pin) Push On Molded Boot -55 to +149 °C		OPTIONAL VERSIONS Optional versions have identical specifications and accessories as listed except where noted below. More than one option may be	
Electrical Impedance Insulation Resistance Physical		50 ohm >10 Tohm	50 ohm >10 Tohm		NOTES: [1] Typical value.	
Electrical Connections(C	center Pin) Shell)	Signal/Power Ground	Signal/Power Ground		Entered: Lef Engineer: Sort Sales Om Approved: B	Spec Number:
Housing Material Finish		Brass Nickel Plated	Brass Nickel Plated		Date: 1-24-12 Date: 1-17-12 Date: 1-17-12 Date: 1-23	51714
Size (Length)  Neight  Neight			[1] [1]	**PCB PIEZOTRONIC5** Phone: 716-684-0001 Fax: 716-684-0987		
ICP® is a registered trademark of PCB Group, Inc.					ELECTRONICS DIVISION 3425 Walden Avenue, Depew, NY 14043  E-Mail: electronics@pcb.c	