

Model Number PR	CABLE CONNECTOR	Revision: NR ECN #: 40084
---------------------------	------------------------	------------------------------

Performance	ENGLISH	SI
Connector Style	D-Sub	D-Sub
Connection Type	9-socket	9-socket
Coupling Method	Jackscrew	Jackscrew
Coupling Thread	4-40 female	4-40 female
Strain Relief	Molded Boot	Molded Boot
Environmental		
Temperature Range	-58 to 212 °F	-50 to 100 °C
Electrical		
Insulation Resistance	1 GOhm	1 GOhm
Physical		
Electrical Connections(Contact 1)	No Connection	No Connection
Electrical Connections(Contact 2)	No Connection	No Connection
Electrical Connections(Contact 3)	No Connection	No Connection
Electrical Connections(Contact 4)	Neg (-) Signal	Neg (-) Signal
Electrical Connections(Contact 5)	Pos (+) Signal	Pos (+) Signal
Electrical Connections(Contact 6)	No Connection	No Connection
Electrical Connections(Contact 7)	Pos (+) Excitation	Pos (+) Excitation
Electrical Connections(Contact 8)	Neg (-) Excitation	Neg (-) Excitation
Electrical Connections(Contact 9)	No Connection	No Connection
Housing Material	Zinc Alloy	Zinc Alloy
Finish	Nickel Plated	Nickel Plated
Size (Length x Height x Width)	1.90 in x 0.63 in x 1.23 in	48.3 mm x 16.0 mm x 31.2 mm
Weight	1.44 oz	40.8 g

All specifications are at room temperature unless otherwise specified.
In the interest of constant product improvement, we reserve the right to change specifications without notice.
ICP® is a registered trademark of PCB Group, Inc.

OPTIONAL VERSIONS

Optional versions have identical specifications and accessories as listed for the standard model except where noted below. More than one option may be used.

NOTES:
[1] Typical.

Entered: AP	Engineer: JDK	Sales: JJM	Approved: APB	Spec Number:
Date: 10/22/2012	Date: 10/22/2012	Date: 10/22/2012	Date: 10/22/2012	54236



3425 Walden Avenue, Depew, NY 14043

Phone: 716-684-0001
Fax: 716-684-0987
E-Mail: info@pcb.com