


Model Number PW	<h1>CABLE CONNECTOR</h1>			Revision: A ECN #: 47295	
Performance Connector Style Connector Style Connection Type Coupling Method(Locking) Strain Relief Environmental Temperature Range Electrical Impedance Insulation Resistance Physical ROHS Compliant Housing Material Finish Size (OD x Length) Weight <i>All specifications are at room temperature unless otherwise specified. In the interest of constant product improvement, we reserve the right to change specifications without notice.</i> ICP® is a registered trademark of PCB Group, Inc.	<u>ENGLISH</u> BNC Coaxial Plug (male pin) Bayonet Molded Boot -85 to 329 °F 50 Ohm 5 GOhm No Brass Nickel Coated .57 in x 1.1 in 0.51 oz	<u>SI</u> BNC Coaxial Plug (male pin) Bayonet Molded Boot -65 to +165 °C 50 Ohm 5 GOhm No Brass Nickel Coated 14 mm x 28 mm 14 gm	OPTIONAL VERSIONS Optional versions have identical specifications and accessories as listed for the standard model except where noted below. More than one option may be used. CT - Cable Type		
Entered: LK		Engineer: RB	Sales: RWM	Approved: BAM	Spec Number:
Date: 9/29/2017		Date: 9/29/2017	Date: 9/29/2017	Date: 9/29/2017	66760
 3425 Walden Avenue, Depew, NY 14043			Phone: 716-684-0001 Fax: 716-684-0987 E-Mail: info@pcb.com		