

	ENGLISH	SI	
Performance			
Connector Style	Multi-conductor	Multi-conductor	
Connection Type	4-socket	4-socket	
Connection Type	Plug with Female Contact	Plug with Female Contact	
Coupling Method	Threaded	Threaded	
Coupling Thread	1/4-28 female	1/4-28 female	
Strain Relief	Molded Boot	Molded Boot	
Environmental			
Temperature Range	-320 to 325 °F	-195 to 162.7 °C	
Physical			
Housing Material	Brass	Brass	
Mounting Torque	25 to 30 in-oz	17.6 to 21.2 N-cm	
Size (OD x Hex x Length)	.34 in x .31 in x 1.0 in	8.6 mm x 7.9 mm x 25.4 mm	
Weight	.11 oz	3.1 gm	[1]

OPTIONAL VERSIONS

Optional versions have identical specifications and accessories as listed for the standard model except where noted below. More than one option may be used.

NOTES:
[1]Typical.

Entered: ND	Engineer: MJN	Sales: BS	Approved: BAM	Spec Number:
Date: 01/12/2026	Date: 01/12/2026	Date: 01/12/2026	Date: 01/12/2026	66867

All specifications are at room temperature unless otherwise specified.
 In the interest of constant product improvement, we reserve the right to change specifications without notice.
 ICP® is a registered trademark of PCB Piezotronics, Inc.

PCB PIEZOTRONICS
AN AMPHENOL COMPANY

Phone: 716-684-0001
 Fax: 716-684-0987
 E-Mail: info@pcb.com

3425 Walden Avenue, Depew, NY 14043