Model Number RG	CABLE CONNECTOR						ision: NR N#: 48998
Performance Connector Style Connector Style Connection Type Coupling Method	ENGLISH Triple Splice SMB Plug with Female Contact Push On	<u>SI</u> Triple Splice SMB Plug with Female Contact Push On	OPTIONAL VERSIONS Optional versions have identical specifications and accessories as listed for the standard model except where noted below. More than one option may be used.				
Strain Relief	Heat Shrink	Heat Shrink					
Environmental							
Temperature Range	-67 to 275 °F	-55 to 135 °C					
Physical							
Electrical Connections	X axis	X axis	Entered: LK	Engineer: KW	Sales: AT	Approved: BAM	Spec Number:
Electrical Connections	Y axis	Y axis	Lillered, LIX	Liigiileei. Kvv	Gales. Al	Approved, BAIVI	Spec Number.
Electrical Connections	Z axis	Z axis	Date: 1/16/2019	Date: 1/16/2019	Date: 1/16/2019	Date: 1/16/2019	70801
ROHS Compliant	Yes	Yes	Date: 1/10/2013	Date: 1/10/2013	Date: 1/10/2013	Date: 1/10/2013	
Size (Length)	12 in	30.5 cm					
All specifications are at room temperature unless otherwise specified. In the interest of constant product improvement, we reserve the right to change specifications without notice.			**PCB PIEZOTRONCS** 3425 Walden Avenue, Depew, NY 14043			Phone: 716-684-0001 Fax: 716-684-0987 E-Mail: info@pcb.com	