


	ENGLISH	SI
Performance		
Connector Style	Triple Splice	Triple Splice
Connector Style	LEMO FGG.1B.307	LEMO FGG.1B.307
Connection Type	7-pin	7-pin
Strain Relief	Molded Boot	Molded Boot
Environmental		
Temperature Range	-40 to 176 °F	-40 to 80 °C
Maximum Shock	100 g pk	981 m/s ² pk
Vibration Survivability	15 g pk	147 m/s ² pk
Physical		
Electrical Connections	"See Outline Drawing"	"See Outline Drawing"
ROHS Compliant	Yes	Yes
Housing Material	Chrome-Plated Brass	Chrome-Plated Brass
Size (OD x Length)	0.47 in x 1.65 in	12 mm x 42 mm

OPTIONAL VERSIONS

Optional versions have identical specifications and accessories as listed for the standard model except where noted below. More than one option may be used.

NOTES:

Entered: LK	Engineer: GD	Sales: KK	Approved: BAM	Spec Number:
Date: 11/30/2020	Date: 11/30/2020	Date: 11/30/2020	Date: 11/30/2020	73221


Phone: 716-684-0001
Fax: 716-684-0987
E-Mail: info@pcb.com
 3425 Walden Avenue, Depew, NY 14043

All specifications are at room temperature unless otherwise specified.
 In the interest of constant product improvement, we reserve the right to change specifications without notice.