



Model SM

5-pin molded Turck Eurofast M12 connector

Installation and Operating Manual

**For assistance with the operation of this product,
contact the PCB Piezotronics, Inc.**

Toll-free: 716-684-0001

24-hour SensorLine: 716-684-0001

Fax: 716-684-0987

E-mail: info@pcb.com

Web: www.pcb.com



Model Number SM		CABLE CONNECTOR						Revision: NR ECN #: 53000	
Performance Connector Style Connector Style Connection Type Connection Type Coupling Method Coupling Thread Strain Relief		ENGLISH Circular Multi-conductor 5-pin Plug (male pin) Threaded No English equivalent Molded Boot		SI Circular Multi-conductor 5-pin Plug (male pin) Threaded M12 x 1 Male Molded Boot		OPTIONAL VERSIONS Optional versions have identical specifications and accessories as listed for the standard model except where noted below . More than one option may be used.			
Environmental Temperature Range Enclosure Rating		-58 to +221 °F IP68		-50 to +105 °C IP68					
Physical ROHS Compliant Housing Material Size (OD x Length) Weight		Yes TPU, Yellow .74 in x 1.87 in 1.0 oz		Yes TPU, Yellow 18.8 mm x 47.5 mm 28.3 g		[1]			
NOTES: [1]Typical.									
Entered: ND		Engineer: GD		Sales: JL		Approved: BAM		Spec Number:	
Date: 07/26/2022		Date: 07/26/2022		Date: 07/26/2022		Date: 07/26/2022		76709	
PCB PIEZOTRONICS AN AMPHENOL COMPANY Phone: 716-684-0001 Fax: 716-684-0987 E-Mail: info@pcb.com 3425 Walden Avenue, Depew, NY 14043									
All specifications are at room temperature unless otherwise specified. In the interest of constant product improvement, we reserve the right to change specifications without notice.									