

<b>Performance</b>	<b>ENGLISH</b>	<b>SI</b>	
Connector Style	Triple Splice	Triple Splice	
Connector Style	Circular	Circular	
Connection Type(X, Y & Z axes)	(3x) 8-Pin	(3x) 8-Pin	
Coupling Method(Keyed)	Snap-on	Snap-on	
Strain Relief	Crimp	Crimp	
<b>Environmental</b>			
Temperature Range	-13 to +176 °F	-25 to +80 °C	
<b>Electrical</b>			
Insulation Resistance(@250V DC)	≥ 50 MOhm	≥ 50 MOhm	
<b>Physical</b>			
Electrical Connections	See Outline Drawing	See Outline Drawing	
ROHS Compliant	Yes	Yes	
Housing Material	Plastic	Plastic	
Size - Length	12 in	305 mm	[1]
Weight	1.25 oz	35.4 g	[1]

**OPTIONAL VERSIONS**

Optional versions have identical specifications and accessories as listed for the standard model except where noted below. More than one option may be used.

**NOTES:**  
[1]Typical.

Entered: ND	Engineer: GD	Sales: BS	Approved: BAM	Spec Number:
Date: 04/10/2025	Date: 04/10/2025	Date: 04/10/2025	Date: 04/10/2025	80321

All specifications are at room temperature unless otherwise specified.  
In the interest of constant product improvement, we reserve the right to change specifications without notice.

**PCB PIEZOTRONICS**  
AN AMPHENÖL COMPANY

Phone: 716-684-0001  
Fax: 716-684-0987  
E-Mail: info@pcb.com

3425 Walden Avenue, Depew, NY 14043